

# LAND CORNER RECORDATION CERTIFICATE

Ontonagon County

LC 5/296

Filing Requirement of Act 74, Mich. P.A. 1970

Date 06/12/2000

Time 16:37:22

RECORDING FEE:

11.00

For corners in

Ontonagon County

Located in:

Corner Code #

1. Public Land Survey

T51N R39W K-1

T R

T R

T R

T R

T R

T R

T R

2. Property Controlling in Section

S

3. Miscellaneous

S

Property in Sec.

S

4. Lot No.

Recorded Plat

5. Private Claims

## SURVEY & REMONUMENTATION

MAR 02 2001

## SECTION

Register of Deeds Stamp &amp; File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Joseph C. Domitrovich, in a field survey on May 22, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(K-1) Closing Corner Sections 1 & 2, T51N, R39W.

1845 - Austin Burt intersected North Boundary 12 links (7.92') East of post and set post, corner of Sections 1 & 2.  
 20" Hemlock S 30°E 50 links  
 10" Sugar S 24°W 43 links

I found no record of subsequent restoration.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found no remains of the original corner or accessories. North - South Calumet Road now runs over corner position. Corner falls at the Northerly Edge of Power line clearing, 50' North of centerline of Power line. I found a 1" diameter iron pipe defining the East R.O.W. of Calumet Road and the Township line. After extensive retracement along the township line, I have determined the true position of the closing corner is best represented by a position in centerline of Calumet Road (33' West of the R.O.W. pipe).

Research on file with County Remonumentation Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 5/8" x 24" iron pin with a 3" diameter aluminum cap stamped to read: COUNTY REMONUMENTATION; T51N, R39W; S. 1, S. 2; C.C.; 2000; P.S. 37273. I also established a Reference Monument (R.M.) to the East, a 2 1/2" x 30" aluminum pipe stamped to indicate that the closing corner is S 89°50'W 23.07'. Ties to the Corner:

8" Basswood	S 45°E	41.07'
Power Pole	S 16°W	142.43'
Standard Corner Sec. 35&36		
T52N, R38W	N 89°57'43"W	7.92'
10" Soft Maple	N 30°E	50.87'
1" R/W Pipe	S 89°57'43"E	33.00'
R.M.	N 89°49'59"E	23.07'
W 1/2 Cor. Sec. 1 (P.K. Nail)	S 00°20'47"E	2625.47' (2614.36' GLO)

See Sketch on Back

NOTE: Bearings to witness objects are magnetic. Distances are to a nail in side of the witness object unless noted.

Signed by

J. C. Domitrovich

Date

5/24/00

Surveyor's Michigan License No. 37273

