

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

Page 1 of 1  
Date 06/12/2000 Time 16:37:02  
RECORDING FEE: 9.00

For corners in

Ontonagon County

Located in:

Corner Code #

1. Public Land Survey

T52N R39W M - 11  
T52N R38W A - 11

2. Property Controlling  
in Section

S  
S

T  
T

R  
R

3. Miscellaneous  
Property in Sec.

S  
S

T  
T

R  
R

4. Lot No.

Recorded Plat

5. Private Claims

**SURVEY &  
REMONUMENTATION**

MAR 02 2001

**SECTION**

Register of Deeds Stamp & File Number

|    | A  | B | C  | D | E  | F | G  | H | I  | J | K  | L | M |
|----|----|---|----|---|----|---|----|---|----|---|----|---|---|
| 1  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 2  | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   |   |
| 3  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 4  | 7  |   | 8  |   | 9  |   | 10 |   | 11 |   | 12 |   |   |
| 5  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 6  | 18 |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |   |   |
| 7  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 8  | 19 |   | 20 |   | 21 |   | 22 |   | 23 |   | 24 |   |   |
| 9  |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 10 | 30 |   | 29 |   | 28 |   | 27 |   | 26 |   | 25 |   |   |
| 11 |    |   |    |   |    |   |    |   |    |   |    |   |   |
| 12 | 31 |   | 32 |   | 33 |   | 34 |   | 35 |   | 36 |   |   |
| 13 |    |   |    |   |    |   |    |   |    |   |    |   |   |

I, Joseph C. Domitrovich, in a field survey on May 22, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(M - 11) Corner Common to Sections 25 & 26, T52N, R39W & Sections 30 & 31, T52N, R38W.

1845 - William A. Burt set a Sugar Post with ties:

|             |        |          |
|-------------|--------|----------|
| 14" Sugar   | S 81°E | 27 links |
| 22" Hemlock | N 56°W | 16 links |

1846 - Sylvester W. Higgins added an additional B.T.

|           |        |         |
|-----------|--------|---------|
| 12" Sugar | N 65°E | 7 links |
|-----------|--------|---------|

I found no record of subsequent restoration.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found no remains of the original corner or accessories. I found East - West paved Firesteel Road and an old Fallen fence running North and South from the corner position. I created a position for the section corner at the intersection of centerline and extension of the fences. This position works well with distances to corners to North and West as well as with occupation. I have determined that this position best represents the true section corner.


Research on file with County Remonumentation Representative.

NEED TOWN APPROVAL  
*Paul W. Applekamp*  
COUNTY REMONUMENTATION  
5-24-00

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 5/8" x 12" iron pin with a 3" diameter aluminum cap stamped to read: COUNTY REMONUMENTATION; T52N, R39W, R38W; S. 25, S. 36, S. 30, S. 31; 2000; P.S. 37273. I also established a Reference Monument (R.M.) to the North, a 2 1/2" x 30" aluminum pipe with a 3" diameter cap stamped to indicate that the section corner is S 01°30'E, 28.11'. Ties to the corner:

|                    |              |                      |
|--------------------|--------------|----------------------|
| 5" Balsam          | S 10°W       | 44.38'               |
| 10" Balsam         | S 35°W       | 49.78'               |
| 9" Soft Maple      | N 52°W       | 58.42'               |
| R.M.               | N 01°30'13"W | 28.11'               |
| E 1/4 Cor. Sec. 25 | N 00°04'29"W | 2655.48'             |
| SW Cor. Sec. 25    | N 89°59'35"E | 5304.33' (P.K. nail) |



NOTE: Bearings to witness objects are magnetic. Distances are to a nail in side of the witness object unless noted.

Signed by

*Joseph C. Domitrovich*

Date

5/24/00

Surveyor's Michigan License No. 37273