

APR 25 1995

COMMISSION

OTSEGO COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 ALSO ACT 345, PA 1990

LIBER 0004 PAGE 012

For corners in

OTSEGO

(County)

Located in:

Corner Code #

1. Public Land Survey

T 29N R 2W

J-3

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

OTSEGO COUNTY
RECEIVED FOR RECORD
94 DEC 14 PM 4:02
LYLLYN M. PRATT
CLERK / REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, James L. Schwandt, in a field survey on November 6, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. Harvey Meilen, September 1856
Set 1/4 Section Post
16" W. Pine N15°W 20 Lks.
12" W. Pine N65°E 31 Lks.

G.F. Delamater, 1925
1/2" x 30" bar
20" Y.P.S. N30°E 50.7'
12" W.P.S. S6°W 60.5'

S. Thorson #5788, 1968
Conc. Mon.
20" Y.P.S. N35°E 50.7'
12" W.P.S. S05°W 60.5'
16" P.S. N27°W 13.0'

Gerald R. McKelvey #19001
October 6, 1976
Fd. Mon. and S. Thorson witnesses
Set Tag 6" J. Pine N12°W 7.91'
Set Tag 20" Pine S65°E 27.10'
Set Tag 6" J. Pine South 15.45'

Carl I. Robinson #16390
April, 1989
Fd. Conc. Mon.
6" R. Pine S15°W 25.70'
20" P.S. S86°W 12.97'
18" P.S. N84°W 20.65'
6" R. Pine N79°W 48.36'


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found concrete monument fitting Delamater's Y.P.S. and W.P.S. Delamater's C.S.R. indicates found Government B & P. Thorson's P.S.; McKelvey's J. Pines; and Robinson's R. Pine all fit the position of this corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-3 Found Conc. Mon. is accepted as a careful and faithful perpetuation of the position of the original corner.

20" J. Pine S80°E 27.10' Found Nail
8" J. Pine South 15.45' Found Nail
12" W.P.S. S06°W 60.52' Found Nail
8" J. Pine N12°W 7.91' Found Nail



OTSEGO COUNTY REMONUMENTATION

Approved by the County Survey Peer
Group, pursuant to Act 345, PA 1990
Dec. 13, 1994
Date Chairman

Signed by James L. Schwandt
James L. Schwandt, PS 26466
Surveyor's Michigan License No.

December 7, 1994