

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:  
OTSEGO  
(County)

Located In

Corner Code #

1. Public Land Survey	T	R	
	T	R	
2. Property Controlling in Section	S 12	T 31N	R 1W 7
	S 12	T 31N	R 1W 14
3. Miscellaneous Property in Section	S	T	R
	S	T	R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on July 31, 2013 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

7 N 1/16 Corner, East line Section 12, T31N,R01W

This corner position was not established during the original Government survey.

14 S 1/16 Corner, East line Section 12, T31N,R01W

This corner position was not established during the original Government survey.



OTSEGO COUNTY MICHIGAN  
RECEIVED FOR RECORD  
SUSAN DEFEYTER, CLERK/REGISTER OF DEEDS  
11/06/2013 1:57:12 PM

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

7 N 1/16 Corner, East line Section 12, T31N,R01W

Established the Southeast corner of the Northeast quarter of the Northeast quarter of section 12 per B.L.M. instructions for the subdivision of a section.  
Set a stamped 2" dia. aluminum cap on 5/8" rebar.

14 S 1/16 Corner, East line Section 12, T31N,R01W

Established the Southeast corner of the Northeast quarter of the Southeast quarter of section 12 per B.L.M. instructions for the subdivision of a section.  
Set a stamped 2" dia. aluminum cap on 5/8" rebar.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

7 N 1/16 Corner, East line Section 12, T31N,R01W

Stamped 2" dia. aluminum cap on 5/8" rebar.

Wit: North 33' to centerline power line right of way  
S86°E 18.42' to set N&T on S side 5" Balsam  
S48°E 3.44' to found 2 1/4" Pipe  
S48°W 16.17' to set N&T on NW side 6" J. Pine  
N53°W 6.34' to set N&T on S side 4" Balsam  
Set Blue Post w/location tag 1' North

14 S 1/16 Corner, East line Section 12, T31N,R01W

Stamped 2" dia. aluminum cap on 5/8"x34" rebar.

Wit: N17°E 27.25' to set N&T on W side 13" W. Pine  
S66°E 54.44' to set N&T on N side 13" W. Pine  
S07°E 31.89' to set N&T on E side 12" W. Pine  
N59°W 45.81' to set N&T on NE side 6" Balsam  
Set Blue Post w/location tag 1' North

Carl T. Kiiskila

Surveyor's Michigan License No.: 33981



11-6-13

LIBER 0009 PAGE 006

LIBER 0009 PAGE 006