

# SURVEY & REMONUMENTATION

OCT 24 1994

COMMISSION

OTTAWA COUNTY REMONUMENTATION

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

94 OCT -7 PM 12:33

*Phyllis Kellman*  
REGISTER OF DEEDS  
OTTAWA COUNTY, MI

For corners in

Ottawa

(County)

Located In:

Corner Code ##

- |                                    |            |                 |
|------------------------------------|------------|-----------------|
| 1. Public Land Survey              | T 6N R 14W | D-3, N 1/4 COR  |
|                                    | T R        | Sec. 8, Blenden |
|                                    | T R        |                 |
|                                    | T R        |                 |
|                                    | T R        |                 |
| 2. Property Controlling in Section | S T R      |                 |
|                                    | S T R      |                 |
| 3. Miscellaneous                   | S T R      |                 |
| Property in Sec.                   | S T R      |                 |

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_

I, Randal D. Feenstra in a field survey on May 9, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. (1932)	Liber 2, Page 585 (1974)	
POST	RR Spike	
10" Black Ash S03°W 19.8	PP	SE 121.50
7" Tree N11°E 22.4	TP	NE 53.86
Samuel Marrs	TP	NW 143.34
	Fence Post	N 29.31

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found: R.R. spike in Mon. Box - accepted as a careful and faithful perpetuation of the position of the original corner.

Found Witnesses:

None & tag E side PP S10°E 101.93  
Portable Nail E side 6" W, 12" S03°W 78.26

P.A. 345 OTTAWA COUNTY

PEER APPROVED

8/22/94

*Robert D. Medwell*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-3 Set O.C. Bar & Cap in Mon. Box	
O.C. Remon. Nail & tag W side 8" Maple	S35°W 78.26
O.C. Remon. Nail & tag W side PP	S10°E 101.93
O.C. Remon. Nail & tag N side 16" Willow	S55°W 138.34
Chisled "X" in 12" conc. culvert	



Signed by Randal D. Feenstra

Date May 9, 1994

Surveyor's Michigan License No. 37275