

SURVEY &
REMONUMENTATION

APR 24 1995

COMMISSION

OTTAWA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

94 DEC 15 AM 11:49

For corners in

Ottawa
(County)

Located in:
Robinson Twp.

Corner Code #

1. Public Land Survey T 7N R 15W K-6
T R W. 1/4 corner
T R Section 13
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds
REGISTER OF DEEDS
OTTAWA COUNTY, MI

Register of Deeds Stamp & File Number

I, Carl P. Englert, in a field survey on November 22, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-6 1/4 corner common to Sections 13 & 14
Original Gov't corner set May, 1832
by Calvin Britain

Set 1/2 mile post
Black Ash 15" S21°E 27 Links
Black Ash 12" N28°W 21 Links

LCRC Liber 3, Page 172 (7/11/77)
Cast Iron Mon.
P.P. N26°E 199.45
4" Ash N62°E 78.35
26" W. Pine S22°E 84.96'
16" Trip. Maple S50°W 49.30'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-6 1/4 corner common to Sections 13 & 14

Found 4" Harrison CIM in Mon. Box 4" deep
Found P.P. N26°E 199.45'
Found 16" Triple Maple S50°W 49.38'

P.A. 345 OTTAWA COUNTY

PEER APPROVED

12/12/94
Richard D. Hedewell

Accepted as a careful and faithful perpetuation of the original position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-6 1/4 corner common to Sections 13 & 14
4" Harrison Cast Iron Mon. in Mon. Box
O.C. Remon. Tag & Nail in N.W. side Trip Maple
O.C. Remon. Tag & Nail in N.E. side 10" Ash
O.C. Remon. Tag & Nail in N. side P.P.
O.C. Remon. Tag & Nail in S.W. side 24" Oak
1/2" Capped Iron Bar

S50°W 49.99'
N41°W 55.80'
N25°E 199.72'
S34°E 57.33'
WEST 33.00'

Signed by

Carl P. Englert Jr.

Date

12/11/94

Surveyor's Michigan License No.

18987

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JANUARY 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

