

1993

1993

COMMISSION

OTTAWA COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

93 DEC 16 PM 1:00

*Shirley A. Sullivan*  
REGISTER OF DEEDS  
OTTAWA COUNTY, MI

For corners in

| Ottawa<br>(County)                    | Located In: | Corner Code ##                  |
|---------------------------------------|-------------|---------------------------------|
| 1. Public Land Survey                 | T 7N R 16W  | H-13 S 1/2 corner<br>Section 34 |
|                                       | T R         |                                 |
|                                       | T R         |                                 |
|                                       | T R         |                                 |
| 2. Property Controlling<br>in Section | S T R       |                                 |
|                                       | S T R       |                                 |
| 3. Miscellaneous<br>Property in Sec.  | S T R       |                                 |
|                                       | S T R       |                                 |

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, THOMAS E. JOINER, in a field survey on 10-28-, 19 93,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Set Cast Iron Monument Midway and on  
Line Between The Southeast And Southwest  
Standard Corners of Section 34 on  
Township Line, Liber 4, Pg. 14

Cast Iron Monument Liber 6, Pg. 71  
12-21-90

West 46.07 to Port Sheldon Corner  
N.W. 37.12 to nail S.E. Side 12" Pine  
N.E. 62.87 to nail S. Side of Power Pole  
S.E. 64.24 to nail N. Side of Power Pole  
S.W. 51.89 to nail E. Side Fence Post

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found cast iron monument and accepted as a careful and faithful perpetuation of the  
position of the original corner.

West 46.07 to Port Sheldon Corner  
N.E. 62.87 to nail S.E. Side of Power Pole  
S.E. 64.24 to nail North Side of Power Pole



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Cast Iron Monument

|                                      |           |        |
|--------------------------------------|-----------|--------|
| O.C. Remon tag & nail 12" White Pine | N. 15° W. | 37.69  |
| O.C. Remon tag & nail Guy Pole       | N. 60° E. | 62.98  |
| O.C. Remon tag & nail Power Pole     | S. 60° E. | 64.03  |
| Northwest House Corner               | S. 05° W. | 112.40 |

Signed by Thomas E. Joiner  
Surveyor's Michigan License No. 18435

Date 11-4-93