

OTTAWA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

97 JUL 24 PM 2:26

Phyllis Ballman
REGISTER OF DEEDS
OTTAWA COUNTY, MI

For corners in

Ottawa

(County)

Located In:

Corner Code ##

- | | | |
|-------------------------|------------|---------------|
| 1. Public Land Survey | T 8N R 13W | A-13 (SW, 31) |
| | T R | Wright Twp. |
| | T R | |
| | T R | |
| | T R | Common Corner |
| 2. Property Controlling | S T R | |
| in Section | S T R | |
| 3. Miscellaneous | S T R | |
| Property in Sec. | S T R | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Donald W. Schiele, in a field survey on March 11, 19 97
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

A-13 SW corner, Section 31, Wright Twp.

Original Government Corner Record:

Corner post of Towns 7 & 8 North, Ranges
13 & 14 West

Post

Sugar 10 in dia bears S54W 10 lks dist

Do 8 " " " N33W 34 " "

John Mullett, Deputy Surveyor

March 13, 1837

L.C.R.C. recorded in Liber 2,

Page 379, 11-19-73

3/4" Pipe in pavement

C/L street sign W 17.70'

Trans. pole SW 102.60'

Tel. pole SE 114.03'

L.C.R.C. recorded in

Liber 3, Page 330,

1-11-79

Found 1" Round Iron by
prev. witnesses

SW to PP 102.63'

SE to PP 114.4'

W. to St. Sign 17.67'

(SEE REVERSE)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-13 Found Cast Iron Monument inscribed "Section Corner", 2" below surface in Monument Box,
and accepted as a careful and faithful perpetuation of the position of the original corner.

Found nail in SW side of Power Pole S22°30'E 114.44'

Found nail & disk in NW side of Power Pole S22°30'E 114.07'

Found nail in NE side of Power Pole S24°W 102.64'

Westerly corner, concrete wingwall to House # 14430

NW corner, foundation to House # 14376

Fd. Ottawa County Remon Tag & nail in West side of Power Pole S22°30'E 114.44'

Fd. Ottawa County Remon Tag & nail in East side of Power Pole S24°W 103.03'

Fd. Ottawa County Remon Tag & nail in East side of Power Pole N13°W 210.38'

Centerline asphalt road North & South, 8' East

On centerline gravel road to East

Field line to West, 18' South

N47°30'E 183.12' (E)

S40°30'E 167.75' (E)

S22°30'E 114.44'

S24°W 103.03'

N13°W 210.38'

PA. 345 OTTAWA COUNTY

PEER APPROVED

4-21-97
ADT

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-13 Cast Iron Monument inscribed "Section Corner", 2" below surface in Monument Box.

Westerly corner, concrete wingwall to House # 14430

NW corner, foundation to House # 14376

Fd. Ottawa County Remon Tag & nail in West side of Power Pole S22°30'E 114.44'

Fd. Ottawa County Remon Tag & nail in East side of Power Pole S24°W 103.03'

Fd. Ottawa County Remon Tag & nail in East side of Power Pole N13°W 210.38'

Centerline asphalt road North & South, 8' East

On centerline gravel road to East

Field line to West, 18' South

N47°30'E 183.12' (E)

S40°30'E 167.75' (E)

S22°30'E 114.44'

S24°W 103.03'

N13°W 210.38'

Signed by

Donald W. Schiele

Date March 15, 1997

Surveyor's Michigan License No.

23517

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

Part A., continued:

L.C.R.C. recorded in Liber 6, Page 91, 1-28-91

A-1, T.7 N., R.13 W.

Set CIM

3" Apple WSW 35.22'

PP SW 102.67'

PP SE 114.45'

14" Elm NW 58.78'

L.C.R.C. recorded in Liber 3, Page 392, 10-24-79

1A, T.7 N., R.13 W.

Found 3/8" Iron

N45°W Guy Pole 100.24'

S45°W N. Line Pymt 10.05'

S20°W MBT Pole 110.90'

Note: This L.C.R.C. not correct location.

Refers to Section 1, T.7 N., R.13 W.

L.C.R.C. recorded in Remon Liber 2, Page 204, 12-15-94

M-13 (T8N, R14W)

Cast Iron Monument inscribed "Section Corner", 2" below surface in Monument Box.

Westerly corner, concrete wingwall to House # 14430 N47°30'E 183.12' (E)

NW corner, foundation to House # 14376 S40°30'E 167.75' (E)

Set Ottawa County Remon Tag & nail in West side of Power Pole S22°30'E 114.44'

Set Ottawa County Remon Tag & nail in East side of Power Pole S24°W 103.03'

Set Ottawa County Remon Tag & nail in East side of Power Pole N13°W 210.38'

Centerline asphalt road North & South, 8' East

On centerline gravel road to East

Field line to West, 18' South