SURVEY & REMONUMENTATION

APR 2:4 1995

COMMISSION

OTTAWA COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A.

RECORDED

94 DEC 15 AM 11: 47

. 1970	Solythia Radinan
	REGISTER OF DEEDS OTTAWA COUNTY, MI

For corners in			D D	EGISTER OF DEEDS	
Ottawa (County)	Located In:	Corner Code ##	Ö	EGISTER OF DEEDS TTAWA COUNTY, MI	
Public Land Survey	T <u>8N</u> R <u>13W</u> T R	C-4 (W%, 8) Wright Twp.			
 Property Controlling in Section Miscellaneous Property in Sec. 	T R S T R S T R S T R	F	Register of Deeds	Stamp & File Numl	ber
	Recorded Plat	•	— <u>A B C D</u>	E F G H I J	K L
			2 6 5 5 3		
, Donald W. Schiele	_ , in a field survey onDe	cember 9, 19 94	4 7 8	9-1-10-1-1-1	 2
in lines 1 and 2 above were current manual of survey ins Management or by a decree of above were in conformance v	in conformance with regulations a tructions of the United States Depa of a Court of Law and/or that The corr with the rules of the Michigan Board	A of 1970, the corner points mentioned nd rules therefore as required in the intent of the interior, Bureau of Land ler points mentioned in lines 3, 4 and 5 of Land Surveyors or by a Decree of a monumented, recovered, found as	6 18 17- 7 8 19 20 9 10 30 29	21 22 23 23 28 27 26	24
NOTE: Not more than 4 on this certificate	corners, all in the same town a e.	and range, may be recorded	11 32 32	33 34 35	36
C-4 % corner comm Original Governmen Set qr sec post be Post	tween Sec. 7 & 8 8 4 uty Surveyor	nd/or subsequent restoration: Wright Twp. L.C.R.C. recorded in Libe Fd. "T" Iron, Set Cast In Power Pole ESE 71. Cross Culvert S 201. St. Sign WNW 30. Power Pole NNW 197.	er 2, Page 72 ron Monument .46' .7'± .85'	9, 1-14-75	
C-4 Found Cast Ir Monument Box, of the origin	ron Monument inscribed , and accepted as a car nal corner. # 16042 in NW side of F	applied in restoring or reestablishing the section Coreful and faithful perpetures S68°E	orner", at su	urface in position	

N08°30'W 197.861 Found nail & Tag # 16042 in South side of Power Pole

Donald W Land Surveyo

P.A. 345 OTTAWA COUNTY

PEER APPROVED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-4 Cast Iron Monument inscribed "Ottawa County Section Corner", at surface in Monument Box.

Set Ottawa County Remon Tag & nail in West side of 6" Pine N20°E 89.76'

Set Ottawa County Remon Tag & nail in SE side of 28" Willow N67°E 97.10'

Set Ottawa County Remon Tag & nail in Newth side of December 12.25 Set Ottawa County Remon Tag & nail in North side of Power Pole Set Ottawa County Remon Tag & nail in SE side of 8" Elm Set Ottawa County Remon Tag & nail in East side of Power Pole Centerline asphalt road North & South, 0.5' East S68°E 71.761

36.17 S57°W N08°30'W 198.231

On centerline gravel road East

On occupation line to West, ±

Surveyor's Michigan License No. _

23517

APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975