

APR 29 1996

COMMISSION

JUDITH D. ROEHM  
Ontonagon County

05/09/95  
13:43

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

3/260 JEM Fee: .00  
Page 1 of 1

For corners in

ONTONAGON

(County)

Located In:

Corner Code #

- |                                    |             |      |
|------------------------------------|-------------|------|
| 1. Public Land Survey              | T 47N R 38W | M-10 |
|                                    | T R         |      |
|                                    | T R         |      |
|                                    | T R         |      |
| 2. Property Controlling in Section | S T R       |      |
|                                    | S T R       |      |
| 3. Miscellaneous                   | S T R       |      |
| Property in Sec.                   | S T R       |      |

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

1/4 Cor. Sections 25 & 30; T.47N., R.37-38W.

I, Richard L. Drahn, in a field survey on December 21, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt, US Deputy Surveyor, in 1847. Original bearing trees:

Sugar	12"	S.70E.	29 links	(19.14 feet)
Sugar	14"	N.22W.	31 links	(20.46 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No G.L.O. evidence remains. Corner position re-established on line between and equal distance from section corners 1/2 mile north and south.

**ONTONAGON COUNTY**

**PEER APPROVED**

*Earl W Applekamp*  
*Ont Co. Rep.*  
*Jan 25, 1995*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 1/2" diameter by 30" long aluminum monument with a 3 1/2" aluminum cap with magnet stamped to read: T.47N., R.37-38W.; 1/4; S-25, S-30; 1994; R.L.S. 21564 from which I established the following new blazed and scribed bearings, trees and/or objects:

12"	Basswood	N.70W.	15.27 feet
10"	Ironwood	N.10W.	28.27 feet
8"	Sugar Maple	S.10W.	7.49 feet
6'	Steel rail	N.15W.	1.09 feet



Signed by Richard L. Drahn

Date January 24, 1995

Surveyor's Michigan License No. 21564

USFS # T-25