

# SURVEY & REMONUMENTATION

APR 25 1995

## COMMISSION

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON

(County)

Located In:

Corner Code #

1. Public Land Survey

T 47N R 39W

D-7

T R

T R

T R

2. Property Controlling in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

Recorded at 11:00 o'clock P.M. 1994  
Liber 3 Page 2195  
Judith Schoen  
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

1/4 Corner, Sections 17, 20; T.47N., R.39W.

I, Richard L. Drahn in a field survey on August 25, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Zelotes B. Searls, U.S. Deputy Surveyor, on June 3, 1851.

Original bearing trees:

Hemlock	12"	S.21°E.	14 links	( 9.24 feet)
Sugar	16"	N.47°W.	21 links	(13.86 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original corner or bearing trees found. Re-established corner position by single proportion measure on a line between the S.E. and the S.W. corners of Section 17.

PEER GROUP

Approved

*Earl W Applekamp* 4-07-94  
Ont Co Rep

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a standard 2" diameter by 30" long split base aluminum monument with a 3 1/4" aluminum cap stamped to read: T.47N., R.39W.; 1/4; S.17., S.20.; 1994; R.L.S. 21564: from which I established the following new blazed and scribed bearing trees and/or reference objects:

12"	Red Maple	N.35°W.	14.68 feet
12"	Sugar Maple	N.64°E.	7.09 feet
10"	Sugar Maple	S.12°E.	10.47 feet

A 6' steel sign post bears: S.55°E. 1.07 feet



Signed by *Richard L. Drahn*

Date February 15, 1994

Surveyor's Michigan License No. 21564

U.S.F.S. N-7

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1993