

SURVEY & REMONUMENTATION

APR 25 1995

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON COMMISSION
(County)

Located In:

Corner Code #

Recorded April 12 1994
at 1:10 o'clock P.M. in
Lib. 3 page 197
J. L. Drahn
Register of Deeds

1. Public Land Survey T 47N R 39W I-6
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

1/2 Corner, Sections 14, 15; T.47N., R.39W.

I, Richard L. Drahn, in a field survey on September 17, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Zelotes B. Searls, U.S. Deputy Surveyor, on June 10, 1851. Original bearing trees:

Hemlock	16"	S.35°E.	11 links	(7.26 feet)
Hemlock	18"	N.45°W.	38 links	(25.08 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original corner or bearing trees found. Re-established corner position on top of ridge, by single proportion measurement on line between the N.E. and the S.E. corner of Section 15.

PEER GROUP

Approved

J. W. Appleby 4-07-94
Ont Co Rep

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a standard 2" diameter by 30" long split base aluminum monument with a 3 1/2" aluminum cap stamped to read: T.49N., R.39W.; 1/4; S.14, S.15; 1993; R.L.S. 21564: from which I established the following new blazed and scribed bearing trees and reference objects:

8"	Sugar Maple	N.68°E.	14.57 feet
12"	Spruce	S.54°E.	11.34 feet
6"	Sugar Maple	S.31°W.	4.01 feet

A 6' steel sign post bears: S.33°W., 0.65 feet



Signed by Richard L. Drahn

Date February 14, 1994

Surveyor's Michigan License No. 21564

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983