

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON

(County)

Located In:

Corner Code #

1. Public Land Survey

T48NR39W

A-8

T48NR40W

M-8

T R

T R

2. Property Controlling  
in Section

S

T R

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

S

T R

SURVEY &  
REMONUMENTATION

MAY 22 1997

COMMISSION

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

$\frac{1}{4}$  Corner common to Sections 19 & 20, T48N R39W. & 40W.

I, Earl W. Applekamp, in a field survey on July 02, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by John Burt, U.S. Deputy Surveyor, July 14, 1847. Set Sugar Maple Post.

ORIGINAL BEARING TREES:

White Pine 30" S20°E 3.30 feet  
Yellow Birch 7" N07°W 16.50 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. There was an old fence, mostly down, running North and West from near the calculated corner position. Corner was re-established by single proportionate measurement and on line with the opposite section corners.

Research on file with the Ontonagon County Remonumentation Program Representative.

PEER GROUP APPROVED

Earl W. Applekamp  
COUNTY REPRESENTATIVE

8-12-96  
9-12-96

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 $\frac{1}{2}$ "x30" aluminum pipe with a 3 $\frac{1}{4}$ " cap stamped to read: County Remonumentation, T48N R39W,  $\frac{1}{4}$ , S19, S24, 1996, P.S. 17610. I established 4 bearing trees and reference objects.

4" Aspen S41°W 8.20 feet - 7" Aspen S40°E 12.18 feet  
7" Aspen N38°W 18.27 feet - Steel sign post East 1.16 feet



Signed by Earl W. Applekamp

Date September 3, 1996

Surveyor's Michigan License No. 17610