

SURVEY & REMONUMENTATION

APR 25 1995

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corner **COMMISSION**

ONTONAGON
(County)

Located In:

Corner Code #

1. Public Land Survey T 48 R 42
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

C-1-2

Other

#4 pm

Recorded Aug 31 1994
at 2:03 o'clock P. M. in
Liber 3 page 202
Julia M. B. Deputy
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

Meander corner, Sections 5 & 6, T48N R42W

I, Earl W. Applekamp, in a field survey on June 06, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt, U.S. deputy Surveyor, August 12, 1848.
Set with Ash Post.

Original bearing trees:

Cedar	8"	S81°W	14 links
Maple	16"	N49°E	36 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found a 1½" pipe on the shore of Lake Gogebic in a channel dug for a small boat. The pipe was 6" below the top of the water. This pipe was used for several surveys in the area, all of which have cottages on small parcels of land. Using this pipe, the recorded descriptions on the East & West fit the occupied land. I monumented the corner, setting it 111 feet North along the Section line from the 1½" pipe to get it out of a man made channel and established the following reference objects.

ONTONAGON COUNTY
PEER APPROVED
Earl Applekamp
8-17-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I set a 2½" x 30" long split base aluminum monument with a 3½" aluminum cap 111 feet North along the Section line from the shore. The monument is set flush with the ground. The cap is stamped: County Monumentation, M.C., S-5, S-6, T48N R42W, 1994, P.S. 17610. I established the following bearing trees and reference objects.

9"	Maple	S68°W	63.88 feet	8"	Maple	N87°E	47.21 feet
3"	Cedar	N33°E	50.18 feet	NW corner			
				house foundation		S29°E	35.03 feet

Signed by Earl W. Applekamp

Date August 10, 1994

Surveyor's Michigan License No. 17610