

DEC 16 1996

COMMISSION

JUDITH D. ROEHM
Ontonagon County
LC 4/ 75 JEM Fees: 9.00
Page 1 of 1

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON
(County)

Located In:

Corner Code #

1. Public Land Survey T48N R42W # 013 pm
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

M.C. common to Section 8 & 9, T48N R42W.

I, Earl W. Applekamp, in a field survey on May 28, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established by Austin Burt, U.S. Deputy Surveyor on August 08, 1848. Set Maple Post.

ORIGINAL BEARING TREES:

Black Ash 12" S45°W 35 links
White Ash 10" S02°E 98 links

PEER GROUP APPROVED

Earl W. Applekamp
COUNTY REPRESENTATIVE
6-06-96

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Lake Gogebic was raised 38" with a dam in 1938. A witness corner to the original meander corner was established on a straight line from the SE Corner of Section 8 and the 1/16 corner (which was set in 1932 from original evidence and found in 1979) projected to the Lakeshore.

Research on file with the Ontonagon County Remonumentation Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 1/2"X30" aluminum pipe with a 3 1/4" cap. This monument is a witness corner to the meander corner and is on the East line of Section 8. The cap is stamped to read: County Remonumentation, T48N R42W, WC, MC, S8, S9, 1996, P.S. 17610. The cap also has an arrow pointing North stamped N00°-26'-49"W, 158.82'. This is the direction and distance to the meander corner. I established the following bearing trees and reference objects.

9" Black Ash S85°-13'-09"W 46.85' - 8" Cedar S77°-21'-04"E 24.63'
7" Black Ash N34°-07'-25"W 18.15' - Steel Sign Post South 1.35'

Signed by Earl W. Applekamp
Surveyor's Michigan License No. 17610

Date May 3, 1996

