REMONUMENTATION

JUDITH D. ROEHM Ontonagon County 10/26/95

LC 3/ 376 MEL 9.00

APR 2 9 1996

LAND CORNER RECORDATION CERTIFICATE

Fee! Page 1

_	COMMISSIO	N Filing Require	ement of Act 74, Mich. i	P.A. 1970								
Fo	ONTONAGON (County)	Located In:	Corner Code #	1								
1.	Public Land Survey	T 49 R 42 T 48 R 42 T R R	B-13									
2.	Property Controlling S	TR										
_	in Section S	TR										
3.		TR		Regist	er of	Deed	ls Sta	8 amı	File	Num	ber	
	Property in Section S	TR										
4	Lot No, Record	led Plat										
	Private Claims				Î	<u> </u>	Ī		g н	11	Ť	L M
	1/4 Corner common to S	Section 6, T48N R	42W & Section 31, 1	149N R42W.	3 - 6		5		j-			-12
do in l ma Ma 5 a De	Earl W. Applekamp, in a f hereby certify that under requirement lines 1 and 2 above were in conform anual of survey instructions of the anagement or by a decree of a Cou- above were in conformance with the cree of a Court of Law; established expressed below:	ents of P.A. 74, Michigan P. nance with regulations and the United States Department of Law and/or that the or the rules of the Michigan B	A. of 1970, the corner points me rules therefore as required in the nent of the Interior, Bureau orner points mentioned in lines oard of Professional Surveyors	entioned e current of Land 3, 4 and s or by a	5	3	20	21		20	3	-2425
-		II 4 II			11	_ _	1		-	-		
N	OTE: Not more than 4 corners, on this certificate.	all in the same town and	range, may be recorded		12 3	,	32-	—33 —	-34-	3; 3;	5—	-36
A.	Description of original monu	iment and accessories a	and/or subsequent restorat	ion:	13	<u> </u>	_l., L		LL,_			
	Original corner estab Surveyor, August 1848			outy								
	ORIGINAL BEARING TREE	is:										

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

29 links

19 links

No original evidence was found. Found a 12" Ash with blazes 18 feet from corner. Blue paint running East from 12" ash. Corner was re-established by single proportionate measurement between opposite section corners East & West.

Research on file with County Remonumentation Program Representative.

AEPHESENTATIVE COUNTY

 C. Description of monument for corner and accessories established to perpetuate locating the position of 	the corner:
--	-------------

At the corner position I set a $2\frac{1}{2}$ "x30" aluminum pipe with a $3\frac{1}{4}$ " cap stamped to read: T48N T49N R42W, $\frac{1}{4}$, S.31, S.6, 1995, P.S. 17610. I established the following bearing trees and reference objects:

12" Ash 10" Maple

S03°E S82°W 32.26 feet 33.94 feet 7" Maple

(19.14 feet)

(12.54 feet)

N50°E

Steel Sign Post North

10.20 feet

1.20 feeto No. 17610 차.

Surveyor's Michigan License No.

8"

811

Sugar

Lynn

N59°E

N38°W

October 03, 1995

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983