

JUDITH D. ROEHN

1P

Ontonagon County

Page 1 of 1

LC 5/269

JEN Date 12/22/1999 Time 14:50:09

RECORDING FEE:

9.00

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON

(County)

Located in:

Corner Code #

1. Public Land Survey

T 49NR 42W

D-9

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

SURVEY &
REMONUMENTATION

MAR 23 2000

SECTION

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____ $\frac{1}{4}$ Corner common to Sections 20 & 29, T49N R42W.

I, Earl W. Applekamp, in a field survey on Nov. 12, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established by William Burt, U.S. Deputy Surveyor, June 16, 1848. Set Sugar Post.

ORIGINAL BEARING TREES:

Sugar 14" North 28 Links (18.48 Feet)
Y. Birch 10" S45°E 15 Links (9.90 Feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. A blue line running East & West crossed over the corner position. I re-established the corner by single proportionate measure and on line between opposite Section Corners East & West.

Research on file with the Ontonagon County Remonumentation Program Representative.

PEER GROUP APPROVED

Earl W. Applekamp 11-30-99
COUNTY REMONUMENTATION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 $\frac{1}{2}$ "X30" split base aluminum pipe with a 3" cap stamped to read: County Remonumentation, T49N R42W, S20, S29, $\frac{1}{4}$, 1999, P.S. 17610. I established three bearing trees and a reference object.

Nail in 8" Sugar Maple S73°W 38.77' - Nail in 7" Sugar Maple S39°E 42.98'
Nail in 6" Sugar Maple N32°E 35.05' - 6' Steel Sign Post North 0.61'

Signed by Earl W. Applekamp
Surveyor's Michigan License No. 17610

Date November 19, 1999