

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Ontonagon	Located In:	Corner Code #
(County)		
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 12 T 51N R 37W	8
	S 12 T 51N R 37W	C-S-NW 1/64
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 8 06/04/2009 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 12) West 1/16 corner Setion 12. Not established in the original survey.

(C-S-NW 1/64 Sec. 12) 1/64 corner being the NE corner of the S1/2 of the SW1/4 of the NW1/4 of
Section 12. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 12) Established the corner midway and on a straight line between Quarter corner 1334.51' west
and the intersection of Quarter lines of Section 12 1334.51' east.

(C-S-NW 1/64 Sec. 12) Established the corner midway and on a straight line between 1/16 corner #8
666.91' south and 1/16 corner #4 666.91' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
17" Hemlock N08W 23.15' mrkd "1/16S BT"
6" Hemlock S88E 14.5' do
11" Cedar S07W 22.95' do
12" Cedar S63W 17.9' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

(1/64) Set 1"IDx32" I.pipe w/ 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of;
10" Maple N40E 15.35' mrkd "1/64S BT"
8" Sugar S31E 10.7' do
8" Maple S31W 13.05' do
7" Maple N71W 7.25' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 06/16/2009

For the Michigan Department of Natural Resources, Office of Land and Facilities

