

DEC 16 1996

**COMMISSION LAND CORNER RECORDATION CERTIFICATE**

Filing Requirement of Act 74, Mich. P.A. 1970

JUDITH D. ROEHM  
Ontonagon County  
LC 4/ 40 JEM Fee: 9.00  
Page 1 of 1

For corners in  
Ontonagon  
(County) Located in: Corner Code #

- |                                       |   |     |   |     |     |
|---------------------------------------|---|-----|---|-----|-----|
| 1. Public Land Survey                 | T | 51N | R | 39W | F-9 |
|                                       | T |     | R |     |     |
|                                       | T |     | R |     |     |
|                                       | T |     | R |     |     |
| 2. Property Controlling<br>in Section | S |     | T | R   |     |
|                                       | S |     | T | R   |     |
| 3. Miscellaneous                      | S |     | T | R   |     |
| Property in Section                   | S |     | T | R   |     |

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Joseph C. Domitrovich, in a field survey on November 2, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

**A. Description of original monument and accessories and/or subsequent restoration:**

(F-9) 1/4 corner common to sections 21 & 28 T51N, R39W

1845 - Austin Burt for William A. Burt, set sugar post.

16" Hemlock S 60° W 24 links

8" Sugar N 70° E 29 links

1949 - U.S. Highway 45 R.O.W. drawings on file at Ontonagon County Courthouse show a distance of 469.50' west of centerline to this 1/4 corner.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

Found a 1 1/4" iron pipe 2' above ground in an old East-West fence. This position works well with section corners to the east and west and with distance east to centerline.

Accepted this position as the 1/4 corner and monumented it as such.

Research on file with County Remonumentation Representative.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

Corner is a 2" x 30" aluminum pipe with a 3" diameter aluminum cap stamped to read: T.51N., R.39W.; 1/4 S. 21, S.28; 1996; P.S. 37273. Corner falls in old east-west fence.

**Witnesses:**

4" Willow	S 35° W	42.32'
7" Willow	N 86° W	35.27'
4" Maple in clump	S 82° E	25.15'
6' steel sign post	South	0.43'

BEER GROUP APPROVED

COUNTY REPRESENTATIVE

05-07-96



**NOTE: Bearings are magnetic. Distances are to nail in side of witness objects unless noted.**

Signed by Joseph C. Domitrovich

Date 4/22/96

Surveyor's Michigan License No. 37273