

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>51</u> N. <u>8</u> S., R. <u>40</u> W.	<u>L7</u>
2. PROPERTY CONTROLLING IN SECTION <u>24</u>	T. <u>51</u> N. <u>8</u> S., R. <u>40</u> W.	<u>2, 1</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ S., R. _____ E. _____ W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER _____

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 5, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner L7: Original monument and accessories not found.

Corner 2: Not set on original survey nor subsequently apparently.

Corner 1: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner L7: Re-established 11-5-76 on line between section corner east and west.

Corner 2: Established 11-5-76 on line between section corner east and one-quarter corner west.

Corner 1: Established 11-5-76 on line between section corner west and one-quarter corner east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>Corner L7</u> : Set 1" I.D. x 36" I.P. with 4" aluminum cap.	<u>Corner 2</u> : Set 1" I.D. x 36" I.P. with 4" alum. cap.
4" Sugar N37°W 4.4 ft. 1/8S, NBT	6" Sugar N41°W 6.1 ft. 1/16S, BT
4" Sugar S10°W 12.8 ft. 1/8S, NBT	5" Sugar S81°W 36.5 ft. 1/16S, BT
3" Sugar S67°E 23.9 ft. 1/8S, NBT	16" Sugar N88°E 14.3 ft. 1/16S, BT
3" Sugar S26°E 2.6 ft. Squared	<u>Corner 1</u> : Set 1" I.D. x 36" I.P. with 4" alum. cap.
	4" Sugar S87°W 16.0 ft. 1/16S, BT
	10" Y.Birch N01°W 26.0 ft. 1/16S, BT
	18" Sugar S38°E 6.4 ft. 1/16S, BT

SIGNED BY Michael W. Roose Michael W. Roose DATE _____
Chief of Survey Party

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE December 28, 1976
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET