

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Ontonagon (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 26 T 51N R 40W S 35 T 51N R 40W S _____ T _____ R _____	J10 8 _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on J10 07/11/2011
8 07/13/2011 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(J10) Center of Section 26. Not established in the original survey.

(8-Sec. 35) West 1/16 corner, Section 35. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(J10) Established the corner at the intersection of straight lines connecting opposite 1/4 corners.

(8-Sec. 35) Established the corner midway and on a straight line between Quarter corner 1304.34' west
and Center of Section 35 1304.34' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(J10) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
5" Maple S83E 27.8' mrkd "C1/4 BT"
4" Ash S50E 25.7' do
5" Maple S17E 36.7' do
9" Poplar S81W 24.2' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

(8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" Ash N47E 31.1' mrkd "1/16S BT"
6" Maple S81E 14.4' do
3" Ironwood S37W 10.35' do
4" triple Y.Birch N44W 9.8' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 08/11/2011

For the Michigan Department of Natural Resources, Forest Management Division

