

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Ontonagon (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 18 T 53N R 37W	16
	S 18 T 53N R 37W	11
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No.	Recorded Plat	
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 16 08/29/2012 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(16-Sec. 18) East 1/16 corner between Sections 18 and 19. Not previously monumented.

(11-Sec. 18) Southwest 1/16 corner, Section 18. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(16-Sec. 18) Established the position for the corner midway and on the Section line between Quarter
corner 1316.75' west and Section corner 1316.75' east.

(11-Sec. 18) Established the position for the corner at the intersection of the South 1/16 line with
the West 1/16 line. I did not run the West 1/16 line parallel with the east Section line, as would
be normal in this fractional section, but ran it slightly more northeasterly so as to more closely
approach the equality of the acreages of the two fractional lots in the SW 1/4, both shown on the
original plat as containing 40.42 acres.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(16) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
7" Sugar N04E 9.8' mrkd "1/16S BT"
4" Sugar N74E 15.85' do
23" Hemlock S28E 11.8' do
5" Maple S20W 20.45' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Hemlock N28W 18.2' mrkd "1/16S BT"
9" Maple N52E 10.9' do
11" Maple S83E 23.55' do
6" Y.Birch S10W 6.7' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by

Stephan J. Szyszkoski

Date

11/29/2012

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources, Forest Resources Division

