

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Ontonagon (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 21 T 53N R 37W	3
	S 21 T 53N R 37W	15
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 3 08/28/2012
15 08/27/2012 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(3-Sec. 21) North 1/16 corner between Sections 20 and 21. Not previously monumented.

(15-Sec. 21) West 1/16 corner between Sections 21 and 28. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(3-Sec. 21) Established the position for the corner midway and on the Section line between Section
corner 1346.66' north and Quarter corner 1346.66' south.

(15-Sec. 21) Established the position for the corner midway and on the Section line between Section
corner 1326.53' west and Quarter corner 1326.53' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
18" Y.Birch N71E 17.2' mrkd "1/16S BT"
11" Hemlock S32E 15.75' do
13" Hemlock N73W 29.1' do
12" Hemlock N43W 21.0' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

(15) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" Sugar N12W 6.85' mrkd "1/16S BT"
6" Sugar N43E 7.0' do
3" Sugar S51E 9.45' do
9" Sugar S46W 9.1' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 11/29/2012

For the Michigan Department of Natural Resources, Forest Resources Division

