## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Ontonagon	Located In:	Corner Code #	
(County)	_		
1. Public Land Survey	T R T R T R T R T R T R T R T R T R T R		
2. Property Controlling in Section	S 15 T 53N R 38W S 15 T 53N R 38W S T R	PCC 2 PCC 3	
3. Miscellaneous Property in Sec.	S T R S T R		Register of Deeds Stamp & File Number
4. Lot No. , Red	corded Plat		ABCDEFGHIJKLM
5. Private Claims			
	PCC2 06/2	21/2010	
ı, Stephan J. Szyszkoski , i	n a field survey on PCC3 06/2	22/2010 do hereby state	
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2			
above were in conformance with regulations and rules therefore as required in the current manual of survey			
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6			
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with 7			
	rd of Land Surveyors or by a Decree	of a Court of Law; established	<sup>1</sup> d, 8 - 19 - 20 - 21 - 22 - 23 - 24 - 2
re-established, monumented, recov	ered, found as expressed below:		9
NOTE: Not more than 2 corron this certificate.	ners, all in the same town and range,	, may be recorded	10 30 29 28 27 26 25 11 1 1 2 31 32 33 34 35 36
A. Description of original monument and accessories and/or subsequent restoration:			

(PCC 2-Sec. 15) Property controlling corner being the Northwest corner of a parcel of land described in L.92 of Deeds, P.41, Ontonagon County Records. This corner is 1600.00 feet north and 208.00' west of the Quarter corner common to Sections 15 and 22.

(PCC 3-Sec. 15) Property controlling corner being the Southwest corner of a parcel of land described in L.92 of Deeds, P.41, Ontonagon County Records. This corner is 208.00' west of the Quarter corner common to Sections 15 and 22, and on the Section line between Sections 15 and 22.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(PCC 2-Sec. 15) Established the corner at a position being 1600.00 feet north along the N-S 1/4 line of Section 15; thence 208.00' west, parallel to the South line of Section 15, from the Quarter corner common to Section 15 and 22.

(PCC 3-Sec. 15) Established the corner 208.00' west of the Quarter corner common to Sections 15 and 22, on the Section line between the Quarter corner and 1/16 corner #15, Sec. 15.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

PCC2-Set 1"IDx32" I.pipe with 4" alum. MDNR cap. PCC3-Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: Set measuring nail with MDNR tag in the side of: mrkd "PCC BT" 9" Maple N21W 18.05' 12" Hemlock N25W 19.4' mrkd "PCC BT" do 9" Cedar N75E 15.0' 12" Cedar S63E 14.9' dΩ 7" Cedar S26E 19.55' do 9" Sugar \$33W 5.6' do 5" Maple \$64W 19.05' 13" Maple N69W 10.25' do Sq'd cedar post adjacent. Bearings magnetic. Sq'd cedar post adjacent. Bearings magnetic.

Signed by

Surveyor's Michigan License No.

Date

08/25/2010

For the Michigan Department of Natural Resources and Environment, Forest Management

FORM APPROVED BY MICHIGAN STATE BOARD

16485 16486

d Jan., 1983 Pervised Oct., 1995

OF MICA

STEPHAN J

SZYSZKOSK LAND

RVEYOR