

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
PRESQUE ISLE
(County)

Located In:

Corner Code ~~##~~

- | | | |
|------------------------------------|-----------------------------|-------------------|
| 1. Public Land Survey | T <u>33N</u> R <u>2E</u> | <u>C-12, D-13</u> |
| | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| 2. Property Controlling in Section | S <u>32</u> T _____ R _____ | <u>10, 15</u> |
| | S _____ T _____ R _____ | _____ |
| 3. Miscellaneous Property in Sec. | S _____ T _____ R _____ | _____ |
| | S _____ T _____ R _____ | _____ |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CARL T. KIISKILA, in a field survey on DECEMBER 12, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-12 D-13 10 15

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-12	D-13	10	15
FD & ACCEPTED A 1 3/4" PIPE W/CONC AS SET BY MARCUS SCHAAF FOR THE E 1/4 COR OF SEC 31. THE COR IS LOCATED IN THE CTR OF A N-S TRAIL AND AT THE S EDGE OF AN E-W TWO TRACK.	FD & ACCEPTED A 2" PIPE W/CONC AS SET BY MICH DEPT OF CONSERVATION SURVEYOR MARCUS SCHAAF FOR THE S 1/4 COR OF SECTION 32. THIS COR WAS ALSO ACCEPTED BY SHELL OIL CO (PERLA STOUT & ASSOC) DURING SUBSEQUENT SURVEYS. PIPE FALLS IN CTR E-W TRAIL ROAD & IS 6' N OF E-W SMOOTH WIRE FENCE.	FD 1 1/2" PIPE AS SET BY MICH DEPT OF CONSERVATION SURVEYOR MARCUS SCHAAF FOR THE SW COR OF THE NW 1/4 OF THE SW 1/4 SEC. 32. MOVED PIPE 3.7' SE TO FIT POSITION PER STANDARD BLM PROCEDURE FOR SUBDIVISION OF A SECTION. COR IS IN THE CTR OF N-S BRUSHED LINE.	FD 1 1/2" PIPE AS SET BY MARCUS SCHAAF FOR THE SW COR OF THE SE 1/4 OF THE SW 1/4 SEC 32. MOVED PIPE 1.28' NW TO FIT POSITION FOR STANDARD BLM PROCEDURE FOR SUBDIVISION OF A SECTION. THE COR IS LOCATED IN THE CTR OF AN E-W TRAIL ROAD & IN LINE W/OLD SMOOTH WIRE TO NORTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-12	D-13	10	15
FD 1 3/4" PIPE IN CONC, SET 5/8"x 32" REBAR W/CAP INSIDE. SET CARSONITE POST 1' NORTH.	FD 2" I.P., 8" BELOW GRADE IN E-W FIRELANE TRAIL RD & OLD FIREBREAK NORTH.	ADJUSTED FD M. SCHAAF 1 1/2" PIPE.	FD & RELOCATED 1 1/2"x 18" I.P. W/ CONC. PLACED CARSONITE POST 16.5' NORTH.
5" OAK N12°W 21.63'	5" OAK S59°W 37.38'	7" W PINE S81°W 11.46'	6" OAK S23°E 9.91'
5" OAK N65°E 35.45'	18" J PINE S22°E 16.24'	6" R PINE SOUTH 21.86'	4" OAK N53°E 21.96'
10" OAK S59°W 17.30'	15" J PINE N81°E 20.64'	14" R PINE N67°E 18.02'	5" OAK N51°W 29.22'
6" OAK S74°E 38.08'	8" OAK N54°E 27.74'	7" SPRUCE N18°W 11.39'	5" OAK S41°W 30.19'
	6" OAK N35°W 39.93'		

\$PERLA STOUT & ASSOC WIT.

Signed by Carl T. Kiiskila Date 4-3-96

Surveyor's Michigan License No. 33981