

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
PRESQUE ISLE
(County)

Located In:

Corner Code ~~##~~

1. Public Land Survey	T 33N R 2E	A-12, B-11
	T R	
	T R	
	T R	
2. Property Controlling in Section	S 31 T R	3, 4
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, CARL T. KIISKILA, in a field survey on DECEMBER 4, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-12 B-11 3

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-12

FD & ACCEPTED A 1 1/2" PIPE W/CONC AS SET BY MICH DEPT OF CONSERVATION SURVEYOR MARCUS SCHAAF FOR THE W 1/4 COR OF SEC. 31.

B-11

FD & ACCEPTED A 1 1/2" PIPE W/CONC AS SET BY MICH DEPT OF CONSERVATION SURVEYOR MARCUS SCHAAF FOR THE N 1/4 COR SEC 31. THIS COR WAS ALSO ACCEPTED BY SHELL OIL CO DURING SUBSEQUENT SURVEYS, (PERLA STOUT & ASSOC.). COR IS IN CTR OF E-W TRAIL.

3

FD THE NW COR OF THE FRAC SW 1/4 OF THE FRAC NW 1/4 SEC 31 AS ESTABLISHED BY M. SCHAAF MICH DEPT OF CONSERVATION SURVEYOR. OLD BRUSH LINES TO NORTH & EAST.

4

ESTABLISHED THE SW COR OF THE NE 1/4 OF THE FRAC NW 1/4 SEC 31 BY STANDARD PROC FOR SUBDIVISION OF A SECTION. OLD E-W BRUSHED-OUT LINE IS 21' SOUTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-12

FD 1 1/2" I.P. ADDED 1" X 36" PIPE W/DNR ALUMN. CAP & SET CARSONITE POST 1' N.

B-11

FD 1 1/2" PIPE W/CONC, SET 5/8" REROD W/CAP INSIDE.

3

FD 1 1/4" X 48" I.P. W/ CONC BASE & SET CARSONITE POST.

4

SET 5/8" X 32" REROD W/CAP & CARSONITE POST.

10" CEDAR N60°W 9.05'
8" MAPLE N10°W 20.45'
8" MAPLE S62°E 20.33'
24" W PINE SOUTH 19.02'
CTR OF 2' WIDE STREAM
WEST 22'

CARSONITE POST DUE N 9.94'
2" BALSAM FIR S60°W 27.36'
3" SPRUCE S09°E 69.15'
13" SPRUCE S68°E 39.21'
*PERLA STOUT & ASSOC. MIT.

10" J PINE S48°W 10.85'
14" R PINE N35°W 39.56'
10" SPRUCE N40°E 25.03'
4" SPRUCE S50°E 7.94'

4" W PINE N31°E 66.08'
3" R PINE N36°W 33.18'
3" R PINE S47°W 12.16'
FD 1 1/4" X 36" GALV
IRON PIPE S66°E 90.48'

Signed by

Carl T. Kiiskila

Date

4-3-96

Surveyor's Michigan License No.

33981