

**1999 PRESQUE ISLE COUNTY, STATE OF MICHIGAN,
LAND CORNER REMONUMENTATION**

DEC 29 1999

LIBER 335 PAGE 222

SECTION

**LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in
PRESQUE ISLE

(County)

Located in: **BISMARCK TWP.** Corner Code # **MPOST**
T 34 N 4 E **10** ✓
 T R
 T R
 T R
 S T R
 S T R
 S T R
 S T R

1. Public Land Survey

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

4. Lot No. _____ Recorded Plat _____
 5. Private Claims _____

Recorded Dec 20, 1999
 At 10:30 o'clock A M
Janet M. Lamb
 Reg. of Deeds, Presque Isle Co. MI

Register of Deeds Stamp & File Number

I, James A. Beck, in a field survey on Nov 30, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Meander point between Secs 31 and 32 on S. side of spit of land in Lake Nettle
 1856 G.L.O. by Alfred Millerd
 "Over Arm of Lake and Set meander post"
 Y. Pine 11 S25E 16
 Y. Pine 10 N23W 17
 Oct 4, 1973 P.A. 132 Survey by Delmer E. Porter RLS 15410
 "South Meander Post"
 1" pinched pipe by old 2"x2" stake 5' from water
 18" Cedar Due North 7.48 feet; 6" Norway S85°W 5.45'
 20" Cedar N50°E 17.70';

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Meander point between Secs 31 and 32 on S. side of spit of land in Lake Nettle
 November 30, 1999 Remonumentation by James A. Beck P.S. 21559
 Found 1" pinched pipe
 N75°W 5.45' P.S. 22428 (R. Bischer) tag in 11" Norway
 N20°E 7.85' " " " " 18" Cedar
 S68°E 17.75' " " " " 16" Cedar

in accordance with P.A. 345
 Chairman Norman J. Quain
 Date 12/14/99

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Meander point between Secs 31 and 32 on S. side of spit of land in Lake Nettle
 November 30, 1999 Remonumentation by James A. Beck P.S. 21559
 1" pinched pipe
 N75°W 5.45' P.S. 22428 (R. Bischer) tag in 11" Norway
 N20°W 24.35' " " " " 11" Cedar
 N20°E 7.85' " " " " 18" Cedar
 S68°E 17.75' " " " " 16" Cedar

Signed by James A. Beck
 Surveyor's Michigan License No. 21559

Date 12-18-1999

