

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

PRESQUE ISLE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 34N R 4E

A-3

T R

T R

T R

T R

2. Property Controlling
in Section

S 7

T R

12

S T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Carl T. Kiiskila, in a field survey on May 20, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-3

12

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY,
AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B"
BELOW.)

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-3

12

Found and accepted a Presque Isle Co. Concrete monument with brass cap for the NW Corner of Sec. 7, as witnessed by Larry Beauregard, P.S.#18654. Fits his L.C.R.C. Pg. 395 and Certificate of Survey Li. 244, Pg. 151.

Established the NE corner of the SE1/4 of the fractional SW1/4 of S-7 per standard BLM instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-3

12

Found Presque Isle Co. Monument.

Tw. Oak	N51°E	66.76'
6" W.Pine	N21°W	25.14'
4" R.Pine	S50°W	29.47'
5" R.Pine	S38°E	55.36'

Set 5/8"x 32" Rerod w/PS cap and carsonite post

5" R.Pine	N01°W	19.70'
12" Oak	N89°E	13.05'
12" Oak	S17°E	13.76'
3" R.Pine	S47°W	13.20'



Signed by Carl T. Kiiskila
Surveyor's Michigan License No. 33981

Date 5-29-97