2201 1995 PRESQUENCE COUNTY STATE OF MICHIGAN REMONUMENTATION ISLE COUNTY RECORDED LAND CORNER RECORDATION CERTIFICATE 95 007 20 PM to 26 JAN 1 7 1996 Filing Requirement of Act 74, Mich. P.A. 1970 For corners in Presque Isle COMMISSION Corner Code ## REGISTER OF DEEDS $_{\rm T}$ 36N $_{\rm R}$ 2E 1. Public Land Survey LIBER 316 PAGE 284 _ R _ **Property Controlling** ___ T ..__ R ... in Section Miscellaneous __ T ____ R __ Register of Deeds Stamp & File Number Property in Sec. __ , Recorded Plat ___ 5. Private Claims __ , ₁₉ <u>9</u>5 Norman J. Quaine in a field survey on April 5 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below: NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: B-5Fd. 2" Pipe GLO Notes 11-6-78 Replaced w/conc mon/brass cap Presque Isle County Resurvey 1856 N50°W 44.31 9" J. Pine S21°W 37.88' 9" J. Pine Sp. Pine 8" N25°W 76 Local Remonumentation Sp. Pine 7" S52°E 67 LCRC Page 341 S52°E 36.27' 8" N. Pine George H. Cannon Delmer E. Porter #15410 B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: B-5 April 5, 1995 Presque Isle County Fd. conc mon/brass cap at C/L fire lanes (S-E-W) S50°E 30.32' 14" N. Pine State Remonumentation Norman J. Quaine #33984 S23°W 37.75' 16" N. Pine N46°W 44.36' 12" J. Pine Porter's Survey P.C. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Ratified by Peer Group Left Conc Mon/Brass Cap in accordance with P.A. S50°E 30.32' 14" N. Pine S23°W 37.75' 16" N. Pine N46°W 44.36' 12" J. Pine S66°W 39.49' 10" J. Pine *Witness tags & nails used. 🕖

Surveyor's Michigan License No. _

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 26, 1977 REVISED MAY 14, 1975 REVISED JAN., 1983