## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	1. PUBLIC LAND SURVEY	т. <u>36</u> е, к. <u>3</u> е	_L-12;	
	2. PROPERTY CONTROLL- 36 ING IN SECTION 36	.,T. 36 N., R. 3 €	5; 12	
	3. MISCELLANEOUS PROPERTY IN SECTION.	, T		
	4. LOT NO, REC	ORDED PLAT		
	5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
	the corner points mentioned in li re-established, monumented, re- and rules therefore as required i Bureau of Land Management or and 5 above were, in a field surve	ines 1 and 2 above were, in monumented, recovered or in the current manual of sur by a decree of a court of latey on	a field survey on <u>SEP</u> restored as expressed be vey instructions of the w. Furthermore, that the 19, found, recover	rements of P.A. 74, Michigan P.A. of 1970, PTEMBER 22 , 1983 , established, elow and in conformance with regulations United States Department of the Interior, the corner points mentioned in lines 3, 4 ered, restored, established or re-established of Registration for Land Surveyors or, by a
	A. Description of original monu	ment and accessories and/o	r subsequent restoration:	
	,			
1:	B. Description of corner evidence 2 - SET CORNER BY STANDA			
.–1: 5	<u>-</u>	ARD SURVEY PROCEDURI	FOR THE SUBIDIV	ISION OF SECTIONS.
	2 - SET CORNER BY STANDA - SET BY STANDARD SUR	ARD SURVEY PROCEDURI	FOR THE SUBIDIV	ISION OF SECTIONS.
5	2 - SET CORNER BY STANDA - SET BY STANDARD SUR	ARD SURVEY PROCEDURI	FOR THE SUBIDIV	ISION OF SECTIONS. F SECTIONS.
5	2 - SET CORNER BY STANDA - SET BY STANDARD SURV - SET CORNER BY STANDARD SURV C. Description of monument for	ARD SURVEY PROCEDURI VEY PROCEDURE FOR TH ANDARD SURVEY PROCEI	E FOR THE SUBIDIV HE SUBIDIVISION O DURE FOR THE SUBD	TISION OF SECTIONS.  F SECTIONS.  IVISION OF SECTIONS.  sating the position of the corner:
5 12	2 - SET CORNER BY STANDARD SURV - SET BY STANDARD SURV - SET CORNER BY STANDARD SURV C. Description of monument for L-12 5/81 ROD W/RLS CAP	ARD SURVEY PROCEDURI  VEY PROCEDURE FOR THE ANDARD SURVEY PROCEI  r corner and accessories estated to the survey proceive setated to the survey processories and survey proceive setated to the survey proceive setated t	E FOR THE SUBIDIV HE SUBIDIVISION OF DURE FOR THE SUBD  blished to perpetuate loc W/RLS CAP N27°E 18.7' S14°E 23.6' S69°E 77.7'	TISION OF SECTIONS. F SECTIONS. IVISION OF SECTIONS.
5 12	2 - SET CORNER BY STANDARD SURV - SET BY STANDARD SURV - SET CORNER BY STANDARD SURV C. Description of monument for L-12 5/81 ROD W/RLS CAP	ARD SURVEY PROCEDURI  VEY PROCEDURE FOR THE ANDARD SURVEY PROCEI  r corner and accessories esta    SET 5/811 ROD A	E FOR THE SUBIDIV HE SUBIDIVISION OF DURE FOR THE SUBD  blished to perpetuate loc W/RLS CAP N27°E 18.7' S14°E 23.6' S69°E 77.7'	TISION OF SECTIONS.  F SECTIONS.  IVISION OF SECTIONS.  Pating the position of the corner:  12  SET 5/8" ROD W/RLS CAP 8" R. OAK N13°E 35.9" 8" CHERRY S23°E 21.1" SET CEDAR POST W/LOC TAG
5 12	2 - SET CORNER BY STANDARD SURY - SET BY STANDARD SURY - SET BY STANDARD SURY - SET CORNER BY ST	ARD SURVEY PROCEDURI VEY PROCEDURE FOR TH ANDARD SURVEY PROCEI  T corner and accessories esta  SET 5/8" ROD V 7" R. OAK 7" R. OAK FENCE CORNER SET POST W/LOX CORNER	E FOR THE SUBIDIV HE SUBIDIVISION OF DURE FOR THE SUBD  WALS CAP N27°E 18.7' S14°E 23.6' S69°E 77.7' C TAG BY	ISION OF SECTIONS.  F SECTIONS.  IVISION OF SECTIONS.  Pating the position of the corner:    12
5 .2	2 - SET CORNER BY STANDARD SURV - SET BY STANDARD SURV - SET CORNER BY STANDARD SURV C. Description of monument for L-12 5/81 ROD W/RLS CAP	ARD SURVEY PROCEDURI VEY PROCEDURE FOR TH ANDARD SURVEY PROCEI  T corner and accessories esta  SET 5/8" ROD V 7" R. OAK 7" R. OAK FENCE CORNER SET POST W/LOX CORNER	E FOR THE SUBIDIV HE SUBIDIVISION OF DURE FOR THE SUBD  WALS CAP N27°E 18.7' S14°E 23.6' S69°E 77.7' C TAG BY	ISION OF SECTIONS.  F SECTIONS.  IVISION OF SECTIONS.  Pating the position of the corner:    12
5 .2	2 - SET CORNER BY STANDARD SURY - SET BY STANDARD SURY - SET BY STANDARD SURY - SET CORNER BY ST	ARD SURVEY PROCEDURI VEY PROCEDURE FOR THE ANDARD SURVEY PROCED TO CORNER SET 5/8" ROD NOT 10 R. OAK FENCE CORNER SET POST W/LOC CORNER  CISTRATION NO. 100	E FOR THE SUBIDIV HE SUBIDIVISION OF DURE FOR THE SUBD  WALS CAP N27°E 18.7' S14°E 23.6' S69°E 77.7' C TAG BY	ISION OF SECTIONS.  F SECTIONS.  IVISION OF SECTIONS.  Pating the position of the corner:    12
5 .2	- SET CORNER BY STANDARD - SET BY STANDARD SURVEYOR'S MICHIGAN RECORDER BY STANDARD STANDARD SURVEYOR'S MICHIGAN RECORDER STATE AND UNITED STANDARD SURVEYOR'S MICHIGAN RECORDER STATE AND UNITED STANDARD SURVEYOR'S MICHIGAN RECORDER STATE AND UNITED STANDARD STANDARD SURVEYOR'S MICHIGAN RECORDER STATE AND UNITED STANDARD SURVEYOR'S MICHIGAN RECORDER STANDARD SURVEYOR'S MICHIGAN RECORDER SURVEYOR	ARD SURVEY PROCEDURI VEY PROCEDURE FOR THE ANDARD SURVEY PROCED  TO CORNER SET 5/8" ROD V TO THE TO	E FOR THE SUBIDIV  HE SUBIDIVISION OF  DURE FOR THE SUBD  WALS CAP  N27°E 18.7'  S14°E 23.6'  S69°E 77.7'  C TAG BY  DATE	ISION OF SECTIONS.  F SECTIONS.  IVISION OF SECTIONS.  Pating the position of the corner:    12
5 12	2 - SET CORNER BY STANDARD  - SET BY STANDARD SURV  - SET CORNER BY STANDARD  C. Description of monument for L-12  5/8" ROD W/RLS CAP  R. OAK S44°E 11.0  R. OAK N9°W 18.2  SIGNED BY SURVEYOR'S MICHIGAN RECEPTOR STATE AND UNITED STANDARD BY SIGNED BY SIGNED BY SIGNED BY	ARD SURVEY PROCEDURI VEY PROCEDURE FOR THE ANDARD SURVEY PROCED  TO CORNER SET 5/8" ROD V TO R. OAK FENCE CORNER SET POST W/LOC CORNER  GISTRATION NO. 100  TATES AGENCIES:	E FOR THE SUBIDIV  HE SUBIDIVISION OF  DURE FOR THE SUBD  WALS CAP  N27°E 18.7'  S14°E 23.6'  S69°E 77.7'  C TAG BY  DATE	ISION OF SECTIONS.  F SECTIONS.  IVISION OF SECTIONS.  Taking the position of the corner:    12