

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Roscommon Located In Corner Code #
1. Public Land Survey T 21N R 3W K13
2. Property Controlling in Section S T R
3. Miscellaneous Property in Section S T R
4. Lot No: Recorded Plat:
5. Private Claims:

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 in a grid pattern.

I, Craig W. McVean, in a field survey on Aug. 19, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- K13 - GLO - Set 1/4 post - J. Brink - 1837
Yellow Pine 17" N47°W 17 L.
Yellow Pine 16" N58°E 15 L.
- Belknap - Fd. US Bearings, no trees for NBT
- M. Schaaf - 1921 - intersect at corner 40.11 1/2 W. of 'L13'.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- K13 - Standard corner common to Section 35 & 36, T21N, R3W- Fd. 2" iron pipe stub in concrete block tablet - down 1.2' - in 'T' gravel road intersection. This is standard Schaaf monument. All GLO BT's gone. 2" iron pipe accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- K13 - Replaced 2' pipe in concrete tablet with 4" DOC (DNR) Brass cap on 1" x 36" Galvanized iron pipe with tin can with concrete around cap, 0.6' below grade.
N45°W 45' to set Blue Carsonite Post with Location tag
S33°W 27.15' to set nail and tag in SE side Utility Pole
N57°W 57.72' to set nail and tag in SW side 4" White Pine
N21°W 66.89' to set nail and tag in E side 9" White Pine scribed 'XBT'
N35°E 43.46' to set nail and tag in NW side 4" White Pine scribed 'XBT'
S89° 47'50" E 780.54' - Grid dist. (780.12' - GLO) along S.L. and 5.58' North at Rt. angle of Standard Line to Fd. 3/4" iron rod - recorded as closing corner - K1, T20N, R3W

Signed by: Craig W. McVean
Surveyor's Michigan License No.: 39088

Date: 12/3/2003

