

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Roscommon
(County)

Located In

Corner Code #

1. Public Land Survey

T 21N R 3W L13

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Section

S T R

S T R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Craig W. McVean, in a field survey on Oct. 27, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

- L13 - GLO - Set 1/4 Post - John Brink - 1837
- Y. Pine 17" N47°W 17 L.

Y. Pine 16" N58°E 15 L.
- Belknapp - Fd. US Bearings - No trees for NBT.

- M. Schaaf - 1921 - East 40.22 CH to "M13."

West 40.11 1/2 CH to "K13."

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- L13 – Standard ¼ corner common to Sec. 36, T21N, R3W – Could find no conclusive evidence of corner. Set 2 ¾" x 21" Harrison Mon. single proportion to GLO between "K13" and "M13". CL. of E-W gravel rd. is 4' N. CL. of firelane N. is 1± E. Set Harrison Monument accepted as a careful and faithful re-establishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- L13 – Stamped Roscommon Co. Harrison Mon. – Down 0.5'
- N15°W 58.22' to set N & T in E. side 21" W. Oak scribed 'XBT'

S60°W 40.88' to set N & T in N. side 16" W. Pine scribed 'XBT'

S20°W 33.30' to set N & T in W. side 8" W. Oak scribed 'XBT'

S50°E 52.97' to set N & T in NE. side 7" R. Maple scribed 'XBT'

N45°E 66' to set blue carsonite post w/ loc. tag



Signed by:

Craig W. McVean

Surveyor's Michigan License No.:

39088

Date:

12/3/2003