

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Roscommon
(County)

Located In

Corner Code #

1. Public Land Survey T 21N R 4W C-11
T 21N R 4W C-12

2. Property Controlling in Section S T R
S T R

3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on October 13, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5			4			3		2	1
3													
4	7		8			9			10		11		12
5													
6	18		17			16			15		14		13
7													
8	19		20			21			22		23		24
9													
10	30		29			28			27		26		25
11													
12	31		32			33			34		35		36
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-11 G.L.O. Artemas Curtis April 1852 set post corner sections 29, 30, 31, and 32.
Wit: W. Pine 7 N63.5°E 17 links
S. Pine 10 S64°W 56 links

C-12 G.L.O. Artemas Curtis April 1852 set quarter section post. Wit: Y. Pine 16 N36°W 1 links
Y. Pine 16 S26°E 32 links

Marcus Schaaf R.L.S. #3104 index shows he set a monument for the section corner common to sections 29, 30, 31, and 32.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

C-11 Found 1 1/2" pipe bent from logging equipment.
Set 1" X 5' pipe with standard DNR cap.

C-12 Set 1" X 4' pipe with standard DNR cap midway and on line between corners C-11 and C-13.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-11 Set 1" X 5' pipe with standard DNR cap.
Wit: 12" Twin Red Pine N52°E 93.36'
10" J. Pine N50°W 58.25'
12" Oak S70°W 62.65'
22" Red Pine S22°E 101.68'
Road intersection N50°E 27'±
Blue Carsonite Post North 1'±

C-12 Set 1" X 4' pipe with standard DNR cap.
Wit: 12" Balsam N16°W 30.70'
9" Maple S75°E 22.25'
12" Twin Maple S01°E 33.41'
11" Spruce N64°W 34.63'
Blue Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

12-4-03

Surveyor's Michigan License No.:

33981

