

# SURVEY & REMONUMENTATION

APR 07 1998

## SECTION

9237

### LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich P.A. 1970

For corners in  
Roscommon County

Located in: Corner Code #

1. Public Land Survey

T23N R1W B-13  
T22N R1W B-1  
T R  
T R

STATE OF MICHIGAN  
ROSCOMMON COUNTY  
RECORDED

16 DEC 97 12:23 P.M.

ROBERT W. SMITH  
REGISTER OF DEEDS

I, Larry L. Cavanagh, in a field survey November, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in line 1 above was in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

FILE IN LIBER 3 OF LAND CORNERS

Register of Deeds Stamp & File Number

A. Description of original monument and accessories and/or subsequent restoration:

JOHN BRINK 1838  
SET POST  
YELLOW PINE 14" N50W 8 LKS  
WHITE PINE 22" N31E 33 LKS

C.F. ROSER 12028 1966  
FD REMAINS OF SQ. CEDAR  
POST AND 2 U.S.BT'S (STUMPS)  
SET 4' X 1" PIPE (6" ABOVE GROUND)  
AND BRANDED CEDAR GUARD  
POST  
16" OAK N50°E 52.79'  
12" J. PINE DUE EAST 50.35'  
14" OAK N70°W 37.93'  
10" OAK S60°W 17.25'  
(US-BT) 18" BLAZED YELLOW PINE  
STUMP N50°W 5.0' (TO FACE)  
(US-BT) 22" BLAZED WHITE PINE  
STUMP N30°E 23.5' (TO FACE)  
CTR OF E-W TRAIL DUE SOUTH 114'

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1" PIPE  
12" J. PINE DUE EAST 50.35'  
11" OAK S60°W 17.03'  
(US-BT) BLAZED YELLOW PINE STUMP N50°W 5.0' (TO FACE)  
US-BT) BLAZED WHITE PINE STUMP N30°E 23.5' (TO FACE)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1" PIPE LEFT IN PLACE. DROVE CAP IN SIDE PIPE STAMPED 17614  
NAIL & TAG IN 5" MAPLE N75°E 30.20'  
NAIL & TAG IN 9" WHITE PINE N25°E 51.41'  
NAIL & TAG IN 10" W. PINE S35°E 42.96'  
NAIL & TAG IN 12" J. PINE DUE EAST 50.35'  
NAIL & TAG IN 11" OAK S60°W 17.03'  
CARSONITE POST NORTH 1.5'

A PERPETUATION OF THE ORIGINAL CORNER.

ROSCOMMON COUNTY  
PEER GROUP APPROVAL  
DATE Dec 5, 1997

Marvin E. Myers, P.S.  
County Surveyor

Signed by  
Surveyor Michigan License NO. 17614

Date Dec. 11, 1997



FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS  
REVISED MAY 14, 1975  
REVISED JAN., 1983

LIBER 3 PAGE 462