

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Roscommon

(County)

Located In

Corner Code #

1. Public Land Survey

T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_

2. Property Controlling  
in Section

S 31 T 22N R 2W 10

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

3. Miscellaneous  
Property in Section

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on January 15, 2008 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

10- This corner position was not established during the original Government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

10- Established the Northwest corner of the Southwest quarter of the Southwest quarter of section 31 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

10- Set a 5/8" X 34" rebar with a P.S. cap #33981

Wit: Set nail and tag on Northeast side of a 8"

White Pine S25°E 12.66'

Set nail and tag on Northeast side of a

12" White Pine S64°E 29.11'

Set nail and tag on West side of a 16" Oak

N25°E 48.37'

Set nail and tag on North side of a 20" Oak

N84°W 141.16'

Center of North - South trail West 10'

Set Blue Carsonite post with location tag 10' East

Signed by:

Carl T. Kiiskila

Date:

2-6-08

Surveyor's Michigan License No.:

33981

