

SURVEY &
REMONUMENTATION

8356

APR 24 1995

ROSCOMMON COUNTY REMONUMENTATION TO BE FILED IN LIBER 3 OF LAND CORNERS

LAND CORNER RECORDATION CERTIFICATE

STATE OF MICHIGAN
ROSCOMMON COUNTY
RECORDED

COMMISSION

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Roscommon

(County)

Located In:

Corner Code ~~##~~

14 NOV 94 3:08 P.M.

1. Public Land Survey

T 22N R 2W

C-7

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

ROBERT W. SMITH
REGISTER OF DEEDS

ROSCOMMON COUNTY

PEER GROUP APPROVAL

DATE 5-10-94

Register of Deeds Stamp & File Number

I, Larry L. Cavanagh, in a field survey on September, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Post set by William Burt 1852

W. Pine 20" N64°W 40 links

Hemlock 20" S19°E 45 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence found

Corner set at double proportionate distance between C-6 - C-8 and A-7 - D-7

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 2 1/2" x 24" cast iron Roscommon County Monument

17614 - 1994

N08°W nail and tag in 20" B. Oak 20.82'

N86°E nail and tag in 6" W. Pine 32.18'

S06°E nail and tag in 24" B. Oak 20.85'

S89°W nail and tag in 8" W. Pine 34.43'

Carsonite post 0.85' North

Is accepted as the best available evidence of the re-establishment of the original corner.



Signed by

Larry L. Cavanagh

Date

Nov. 14, 1994

Surveyor's Michigan License No.

17614

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

LIBER 3 PAGE 137