

SURVEY & REMONUMENTATION

APR 07 1998

98 SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich P.A. 1970

STATE OF MICHIGAN
ROSCOMMON COUNTY
RECORDED

For corners in
Roscommon County

Located in:

Corner Code #

1. Public Land Survey

T22N R2W
T____R____
T____R____
T____R____

J-7

16 DEC 97 12:27 P.M.

ROBERT W. SMITH
REGISTER OF DEEDS

FILE IN LIBER 3 OF LAND CORNER

Register of Deeds Stamp & File Number

I, Larry L. Cavanagh, in a field survey October, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in line 1 above was in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

A. Description of original monument and accessories and/or subsequent restoration:

WILLIAM BURT 1852
SET POST
CEDAR 4 S61E 18 LKS
CEDAR 8 N61W 18 LKS

GEO D. HENNING 1965
SET 5/8" BAR AND POST (PROP)
8" MAPLE S5°W 8.7'
9" MAPLE N35°E 44.7'
18" PINE STP. N30°W 20.15'

NORMAN C. CALDWELL RLS 12018
APRIL 1963
SET 5/8" BAR
18" PINE STUMP N30°W 20.15'
9" MAPLE N35°E 44.68'
8" MAPLE S05°W 8.90'

LCRC L2 P193 1970'S
5/8" IRON BAR
S5°W 8.90 8" MAPLE
N35°E 44.68' 9" MAPLE
N30°W 20.15' 18" PIPE STUMP

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 5/8" BAR
8" MAPLE S5°W 8.9'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET ROSCOMMON COUNTY MONUMENT STAMPED 17614, 1997
NAIL & TAG IN 10" TWIN MAPLE S5°W 8.55'
NAIL & TAG IN 10" MAPLE N64°W 20.95'
NAIL & TAG IN 6" MAPLE N55°E 15.75'
NAIL & TAG IN 8" MAPLE S65°E 22.50'
CARSONITE POST NORTH 1.27'

A CAREFUL AND FAITHFUL ESTABLISHMENT OF THE POSITION OF THE CORNER.

ROSCOMMON COUNTY
PEER GROUP APPROVAL
DATE DEC 5, 1997

Marvin E. Myers
Marvin E. Myers, P.S.
County Surveyor



Signed by *Larry L. Cavanagh*
Surveyor's Michigan License NO. 17614

Date Dec. 11, 1997

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

LIBER 3 PAGE 472