

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Roscommon Located In Corner Code #
(County)
1. Public Land Survey T R
2. Property Controlling in Section S 25 T 22N R 2W 13
3. Miscellaneous Property in Section S T R
4. Lot No: Recorded Plat:
5. Private Claims:

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 and two black dots in row 11, column M.

I, Carl T. Kiiskila, in a field survey on August 17, 1999 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
13-This corner was position was not established during the original government survey.
16-This corner was position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:
13- Found and accepted a 1/2" iron rod with a RLS cap #2240 as set by G. Henning RLS #2240 c. 1970. This position fits BLM standards for subdivision of a section.
16- Found and accepted a 1/2" iron rod with RLS cap #2240 as set by G. Henning RLS #2240 c. 1970. This position fits BLM standards for subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Table with 2 columns: 13- 1/2" iron rod with RLS cap #2240 and 16- 1/2" iron rod with RLS cap #2240. Rows include Wit: 14" Oak, 5" Oak, 8" Oak, 14" Oak and bearings/distances like N09°W 11.43', N74°W 17.45', S50°W 9.00', S22°E 32.20', N14°W 54.25', N28°E 35.48', S57°W 28.57', S02°E 28.40'.

Signed by: Carl T Kiiskila
Surveyor's Michigan License No.: 33981

Date: 9-8-99

