## LAND CORNER RECORDATION CERTIFICATE

	Filing Requir	rement of Act 74, Mich. P.	A. 1970						
For corners in									
Roscommon	Located In:	Corner Code ##				•			
(County)									
1. Public Land Survey	T <u>23N</u> R <u>3W</u> T <u>23N</u> R <u>3W</u> T <u>23N</u> R <u>3W</u>	K-3 J-3 L-3							
2. Property Controlling in Section	· — · — ·								
3. Miscellaneous Property in Sec.	S T R S T R		Registe	r of Deed	s Stam	ıp & Fil	e Num	nber	
	, Recorded Plat			A B C	D E F	F G H	, , <u>,</u>	<u> </u>	Ţ
			3						+
Carl R. Johnson	1 , in a field survey on	June 1	39 . s			10		<u>'</u>	-12-
do hereby certify that under in lines 1 and 2 above were	requirements of P.A. 74, Michigan P.A re in conformance with regulations a	A. of 1970, the corner points mention and rules therefore as required in	ned 6 the	1 <b>8</b> 1	7———16	;		-	 -13- 
Management or by a decree above were in conformance	astructions of the United States Depa of a Court of Law and/or that the corn with the rules of the Michigan Board	er points mentioned in lines 3, 4 a of Land Surveyors or by a Decree	nd 5 a	-192	21		23	十	<b>1</b>
Court of Law; established expressed below:	d, re-established, monumented, re-	-monumented, recovered, found	jas 10	_302	28	, 27	26	,	-25

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded

A. Description of original monument and accessories and/or subsequent restoration:

- K-3 Set by double proportionate measurement. No other evidence available.
- J-3 Set at found old square stake believed to be set by Ostling. Possible original "BT" SE.
- L-3 Set midway and on line between section corners fits call to swamp edge no other evidence available.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3 - SW Cor. Sec. 1 D.N.R. Monument D.N.R. Monument
10" Double Maple N6 E 19.5'
8" D. White Birch S44 E 32.5'
8" Maple S21 W 33.8'
8" Maple N54 W 34.0'

on this certificate.

 $J-3-S_4$  cor. Sec. 2 D.N.R. Monument Possible O.B.T. Stump S26 E 35.4' Maple N44 E 91.8'

L-3 - S\(\frac{1}{4}\) cor. Sec. 1

D.N.R. Monument

5" Maple N76 W 41.0'

6" Maple N11 E 74.1'

**JOHNSON** LAND SURVEYOR

30083 Surveyor's Michigan Lice se No. \_

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983