

**ROSCOMMON COUNTY  
PEER GROUP APPROVAL**

**DATE** 12-28-94

**ROSCOMMON COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

JAN 24 1995

COMMISSION

For corners in

ROSCOMMON

(County)

Located In:

Corner Code #

TO BE FILED IN LIBER 3 OF LAND CORNERS

1. Public Land Survey

T 23N R 4W

M-7

T      R     

T      R     

T      R     

2. Property Controlling  
in Section

S      T      R     

S      T      R     

3. Miscellaneous  
Property in Sec.

S      T      R     

S      T      R     

APR 05 1995

COMMISSION

STATE OF MICHIGAN  
ROSCOMMON COUNTY  
RECORDED

28 DEC 94 1:06 P.M.

Register of Deeds Stamp & File Number  
ROBERT H. SMITH  
REGISTER OF DEEDS

4. Lot No.         , Recorded Plat         

5. Private Claims         

Timothy L. Lapham, in a field survey on December, 19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

M-7: 1838 BRINK, SET POST, BIRCH 10" N61W 15LK., CEDAR 10" S37W 32 LK.

SURVEYOR/DATE UNKNOWN, LCRC 2-377, 1" PIPE, 3 WITNESSES

9/1943 HENNING SURVEY, NO CORNER MATERIAL OR WITNESSES

6/01/1979 CAVANAGH SURVEY 365-157, 1" PIPE, SAME 3 WITNESSES AS 2-377

1/19/1980 CAVANAGH LCRC 1-201, 1/2" BAR SAME 3 WITS PLUS 1 ADDITIONAL

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-7: FOUND 1"x32" PIPE EXCAVATED TO 3' FOUND 1/2"x36" IRON BAR, FOUND 2 WITNESSES AND STUMP OF THIRD, DISTANCES N AND W MATCH HENNING SURVEY, ACCEPTED FOUND IRON AS BEST EVIDENCE OF ORIGINAL CORNER POSITION. CORNER APPROVED AT PEER REVIEW MEETING 12-28, 1994. SEE DOSSIER FOR ADDITIONAL INFORMATION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-7: SET 2-1/2"x24" CAST IRON MONUMENT WITH BRASS DISC MARKED 1994-27595

N60W 41.52 SET NAIL AND TAG SW FACE 16" MAPLE

N45E 63.51 SET NAIL AND TAG NW FACE 16" MAPLE

WEST 33.00 FACE OF CARSONITE POST

S58E 61.43 SET NAIL AND TAG IN NE FACE 8" FIR

EAST 32.25 1" AXLE SHAFT

Signed by

Date

Surveyor's Michigan License No. 27595