2921

5. Private Claims

OCT 0 5 1998

SECTION Filing Requirement of Act 74, Mich. P.A. 1970 STATE OF MICHIGAN For corners in ROSCOMMON COUNTY RECORDED Located in: Corner Code # Roscommon (County) 20 APR 98 2:18 P.M. T 24N_R _1W 1. Public Land Survey ROBERT W. SHITH T 23N R 1W REGISTER OF DEEDS R R To be filed in Liber 3 of Land 2. Property Controlling R S Corners in Section S R 3. Miscellaneous R Register of Deeds Stamp & File Number R Property in Sec.

LAND CORNER RECORDATION CERTIFICATE

I, Marvin E. Myers, in a field survey on _March 2_, 1998_do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

G.L.O - 1838 Lewis Clason, DS Mon. - Post 10° Tamarack N39°E 20 links 9" Tamarack N58 1/2°W 34 links

, Recorded Plat

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1 1/2"x36" pipe 1' above grade with old 4" x 4" post 0.5' South. I believe this is a Schaaf monument set in the swamp without a concrete base. Accepted as the best available evidence of the position of the Original Corner. Replaced Pipe with Standard Roscommon County Monument.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon - Standard Roscommon County Monument.

Wit: Set carsonite Post 1' South.

Set nail & tag in East face 3" Tamarack S37°W 48.52' Set nail & tag in North face 4" Tamarack N56°W 42.10" Set nail & tag in East face Power Pole N28°W 193.56' Set nail & tag in West face Power Pole N63°E 278.51'

> **ROSCOMMON COUNTY PEER GROUP APPROVAL** DATE MARCH 27 4 1998

Marin E. Myen Will

County Surveyor Signed by _



Date April 10, 1998

Surveyor's Michigan License No. 31600

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS

LIBER 3 PAGE 494