## ROSCOMMON COUNTY REMONUMENTATION

9249 994

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Dec 28 10 47 AH \*93

7	Rose
1. Public Land Survey    T	• • •
T R T R DATE  I R T R DATE  IN Section S T R R R  IN Section Register  Properly in Sec. S T R R R  In Section Register  Register  Properly in Sec. S T R R R  In Section Register  Regis	REGIST:
T R T R DATE  I R R DATE  I R R DATE  In Section S T R R R R  In Section S T R R R  In Section Register  Properly in Sec. S T R R R  In Section Register  Properly in Sec. S T R R R  In Section Register  Register  Properly in Sec. S T R R R  In Section Register  Register  Register  Private Claims  Frank J. Arleth in a field survey on December 19 93  In Section Register  Private Claims  Frank J. Arleth in a field survey on December 19 93  In Section Register  Private Claims  Frank J. Arleth in a field survey on December 19 93  In Section Register  Private Claims  Frank J. Arleth in a field survey on December 19 93  In Section Register  Properly in Sec. S T R R R Register	
PERRY DATE  T R R T R R T R R A R A Miscellaneous S T R R A R A Register  Properly in Sec. S T R R A R A Lot No. Recorded Plat  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on Interest on the sequired in the curve of the Court of Interest on the Interest on Interest o	OMMON COUNTY
2. Properly Controlling S T R R R Register  in Section S T R R R Register  Property in Sec. S T R R R Register  4. Lot No. Recorded Plat  5. Private Claims Private Claims  Frank J. Arleth in a field survey on December 19 93  do hereby certify that under requirements of PA 74 Michigan PA of 1970, the corresponits mentioned district and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior. Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in the Survey as Decree of a Doort of Law and/or that the corner points mentioned in the Survey as Decree of a Doort of Law and/or that the corner points mentioned in the Survey as Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Doort of Law and/or that the corner points mentioned in the Survey as Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Survey scalable of the Michigan Board of Land Surveyors or by a Decree of a Survey Sur	GROUP APPROVAL
in Section  S T R  Miscellaneous S T R  Miscellaneous S T R  Lot No Recorded Plat  Lot No Recorded Plat  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on December  Frank J. Arleth in a field survey on Interest on Inte	12-14-93
3. Miscellaneous S T R R Register Property in Sec. S T R R Register Property in Sec. S T R R R Register Property in Sec. S T R R R Register Property in Sec. S T R R R R Register Property in Sec. S T R R R R R R R R R R R R R R R R R R	76-74-75
Property in Sec. S T R	
Frank J. Arleth in a field survey on December 19 93  Frank J. Arleth in a field survey on December 19 93  for hereby certify that under requirements of P.A. 74. Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the jument of survey instructions of the United States Department of the Interior, Bureau of Land danagement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" S18% 14 Lks.  W. Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Cedar N35°W 67.77  10" Cedar N35°W 67.77  10" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the post set in 8" Cedar N35°W 67.77  Spike in 18" Cedar N36W 67.77  Spike in 10" Cedar N36W 67.77  Spike in 10" Cedar N39°E 54.11  Nail & tag in 10" Cedar N36°E 51.15  Carsonite post set 33.0 North	er of Deeds Stamp & File Number
Frank J. Arleth in a field survey on December 19 93  Frank J. Arleth in a field survey on December 19 93  To hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the survent manual of survey instructions of the United States Department of the Interior, Eureur of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Department of the Interior, Eureur of Law and 5 above were in conformance with the rules of the Michigan Department of the Interior Surveyors or by a Decree of a sourt of Law, established, re-established, monumented, re-monumented, recovered, found as surpressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt's set post 1852 Cedar 12: \$1887 14 Lks.  W. Birch 8" N10°E 43 Lks.  3. Description of corner evidence found and/or method applied in restoring or reestablishing corners and survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N35°W 67.77  10" Cedar N36°W 67.77  Cedar N36°W 67.77  Spike in 8" Cedar N36°W 67.77  Spike in 10" Cedar N39°W 55.411  Spike in 12" Cedar N39°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
Frank J. Arleth in a field survey on December 19 93  To hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the survent manual of survey instructions of the United States Department of the Interior, Eureur of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 to brow were in conformance with the rules of the Michigan Bopartment of the Interior, Eureur of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 to brow were in conformance with the rules of the Michigan Bopartment of the Interior, Eureur of Law and 5 to Law an	
Frank J. Arleth in a field survey on December 19 93  To hereby certify that under requirements of P.A. 7.4. Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management of by a decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" S18% 14 Lks.  W. Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Cedar N35°W 67.77  10" Cedar N35°W 67.77  10" Cedar N39°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the pose of Roscommon Country Std. Mon Stamped G = 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N39W 75.41  Spike in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	A B C D E F G H I J K L
Frank J. Arleth in a field survey on December 19 93 6 10 hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the urrent manual of survey instructions of the United States Department of the Interior, Bureau of Land Rangement of by a decree of a Court of Law and/or that the corner points mentioned in the survey instructions of the United States Department of the Interior, Bureau of Land Survey or by a Decree of a bove were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a bove were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Sourt of Law; established, re-established, monumented, re-monumented, recovered, tound as xpressed below.  IOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1952 Cedar 12" S18 % 14 Lks.  W. Birch 8" N10°E 43 Lks.  Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3" deep in centerline of E&W blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½" bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  Description of monument for corner and accessories established to perpetuate locating the pose Set Roscommon Country Std. Non Stamped G = 8  Spike in 10" Cedar N39W 75.41  Spike in 10" Cedar N39W 75.41  Spike in 10" Cedar N39W 75.41  Spike in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
Cheebey certify that undor requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the furrent manual of survey instructions of the United States Department of the Interior, Bureau of Land danagement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 bove were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as xpressed below:  ***********************************	┟╌╀╼╂╌╂╌╂╌╂╌╂╌╂
In the top to certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points emitioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the furrent manual of survey instructions of the United States Department of the Interior. Bureau of Land Stanagement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 bove were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as xpressed below:  10 Expressed below:  11	
n lines 1 and 2 above were in conformance with regulations and rules therefore as required in the unrent manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 bove were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" \$18 W 14 Lks.  W. Birch 8" N10°E 43 Lks.  3. Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of E&W blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½" bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar \$26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the positive in 8" Cedar N35°W 67.77  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 10" Cedar N3°W 75.41'  Spike in 10" Cedar N3°W 75.41'  Spike in 10" Cedar N36°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
A. Description of corner evidence found and/or method applied in restoring or reestablishing corner 1981 Wilcox Found 1" iron rod 3" deep in centerline of E&W blacktop with rerod & cap.  1981 Wilcox Found 1" iron rod 3" deep in centerline of E&W blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½" bar in blacktop and found 8" Cedar N35°W 67-77  10" Cedar N03°W 75-41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  Description of monument for corner and accessories established to perpetuate locating the postike in 8" Cedar N35°W 67-77  Spike in 10" Cedar N39°W 75-41  Spike in 12" Cedar N19°E 54.11  Naii & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	18 17 16 15 14 17
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" S18% 14 Lks.  W. Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of E&W blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½" bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the post of the stable of the perpetuate in 10" Cedar N35°W 67.77  Spike in 8" Cedar N35°W 75.41'  Spike in 10" Cedar N3°W 75.41'  Spike in 10" Cedar N3°W 75.41'  Spike in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" S18 W 14 Lks.  W. Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Cedar N35°W 67-77  10" Cedar N35°W 67-77  10" Cedar N35°W 67-77  Cedar N35°W 54-11  6" Cedar S26°E 51-10  C. Description of monument for corner and accessories established to perpetuate locating the post in 8" Cedar N35°W 67-77  Spike in 8" Cedar N35°W 67-77  Spike in 10" Cedar N39°W 75-41  Spike in 10" Cedar N39°W 75-41  Spike in 10" Cedar N39°W 75-41  Spike in 10" Cedar N39°W 57-77  Spike in 10" Cedar N39°W 57-77  Spike in 10" Cedar N39°W 57-41  Spike in 10" Cedar N39°W 57-41  Spike in 10" Cedar N35°W 67-77	19 20 21 4 22 23 23 2
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration: William Burt set post 1852 Cedar 12" \$18 \text{ Vi 14 Lks.} W. Birch 8" \$N10^0\text{ E 43 Lks.}  3. Description of corner evidence found and/or method applied in restoring or reestablishing corners 1981 Wilcox Found 1" iron rod 3" deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found \(\frac{1}{2}\)" bar in blacktop and found 8" Cedar \$N35^0\)W 67.77 10" Cedar \$N03^0\)W 75.41 12" Cedar \$N19^0\text{ E 4.11} 6" Cedar \$26^0\text{ E 51.10}  C. Description of monument for corner and accessories established to perpetuate locating the posent set in 10" Cedar \$N30\)W 75.41  Spike in 8" Cedar \$N35^0\)W 67.77 Spike in 10" Cedar \$N30\)W 75.41  Spike in 12" Cedar \$N19^0\text{ E 4.11}  Nai1 & tag in 10" Cedar \$260\text{ E 51.15}  Carsonite post set 33.0 North	
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" \$18 % 14 Lks.  W. Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½" bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar \$26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset set as a certain 10 Cedar N36°W 67.77  Spike in 8" Cedar N35°W 67.77  Spike in 10 Cedar N39°W 75.41'  Spike in 10 Cedar N19°E 54.11  Nai1 & tag in 10" Cedar \$260E 51.15  Carsonite post set 33.0 North	30 29 28 27 26 2
on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" \$18°\text{if 14 Lks.} W. Birch 8" \$N10°\text{E}\$ 43 Lks.  Company found \$\frac{1}{2}\$" bar in blacktop and found \$\frac{8}{2}\$" Cedar \$N35°\text{W}\$ 67.77  Cedar \$N39\text{W}\$ 75.41  Cedar \$N26°\text{E}\$ 51.10  C. Description of monument for corner and accessories established to perpetuate locating the post \$\text{Set}\$ Cedar \$N35°\text{W}\$ 67.77  Spike in 8" \$\text{Cedar \$N35°\text{W}\$ 67.77  Spike in 10" \$\text{Cedar \$N39\$\text{W}\$ 75.41'  Spike in 10" \$\text{Cedar \$N19°\text{E}\$ 54.11  Nail \$\text{ tag in 10" \$\text{Cedar \$N26°\text{E}\$ 51.15}  Carsonite post set 33.0 North	
Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" S18% 14 Lks. W. Birch 8" N10°E 43 Lks.  Birch 8" N10°E 43 Lks.  Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½" bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  Description of monument for corner and accessories established to perpetuate locating the post Set Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 10" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
Description of original monument and accessories and/or subsequent restoration:  William Burt set post 1852 Cedar 12" \$18 \text{V} 14 Lks. W. Birch 8" \$N10^6 E 43 Lks.  Bescription of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found \( \frac{1}{2} \) " bar in blacktop and found 8" Cedar \$N35^6 W 67.77  10" Cedar \$N03^0 W 75.41  12" Cedar \$N19^6 E 54.11  6" Cedar \$26^6 E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the post Set Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar \$N35^0 W 67.77  Spike in 10" Cedar \$N36^0 F 54.11  \$N31 & tag in 10" Cedar \$N26^0 E 51.15  Carsonite post set 33.0 North	
William Burt set post 1852 Cedar 12" \$18 \text{W} 14 Lks.  W. Birch 8" \$N10^\text{E}\$ 43 Lks.  Birch 8" \$N10^\text{E}\$ 43 Lks.  Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of E&W blacktop with rerod & cap.  1993 Arleth Land Survey Company found \( \frac{1}{2} \)" bar in blacktop and found 8" Cedar \$N35^\text{W}\$ 67.77  10" Cedar \$N03^\text{W}\$ 75.41  12" Cedar \$N19^\text{E}\$ 54.11  6" Cedar \$26^\text{E}\$ 51.10  C. Description of monument for corner and accessories established to perpetuate locating the post Set Roscommon County \$td\$. Mon Stamped \$G - 8\$  Spike in 8" Cedar \$N35^\text{W}\$ 67.77  Spike in 10" Cedar \$N35^\text{W}\$ 67.77  Spike in 10" Cedar \$N3^\text{W}\$ 75.41  Nail & tag in 10" Cedar \$S26^\text{E}\$ 51.15  Carsonite post set 33.0 North	
Cedar 12" \$18 \text{W} 14 Lks.  W. Birch 8" \$N10^\text{E}\$ 43 Lks.  B. Description of corner evidence found and/or method applied in restoring or reestablishing corner 1981 Wilcox Found 1" iron rod 3' deep in centerline of E&W blacktop with rerod & cap.  1993 Arleth Land Survey Company found \( \frac{1}{2} \) " bar in blacktop and found 8" Cedar \$N35^\text{W}\$ 67.77  10" Cedar \$N03^\text{W}\$ 75.41  12" Cedar \$N19^\text{E}\$ 54.11  6" Cedar \$26^\text{E}\$ 51.10  C. Description of monument for corner and accessories established to perpetuate locating the posential section of the section o	
B. Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of E&W blacktop with rerod & cap.  1993 Ar1eth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
B. Description of corner evidence found and/or method applied in restoring or reestablishing corn 1981 Wilcox Found 1" iron rod 3' deep in centerline of E&W blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the posence of the second of the	
1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N36°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
1981 Wilcox Found 1" iron rod 3' deep in centerline of ESW blacktop with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N36°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	ner:
with rerod & cap.  1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
1993 Arleth Land Survey Company found ½ " bar in blacktop and found 8" Cedar N35°W 67.77  10" Cedar N03°W 75.41  12" Cedar N19°E 54.11  6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the posent set as a spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N35°W 67.77  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	Rodu. Raiseu
8" Cedar N35°W 67.77 10" Cedar N03°W 75.41 12" Cedar N19°E 54.11 6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10"Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	Wilcox wite
10" Cedar N03°W 75.41 12" Cedar N19°E 54.11 6" Cedar S26°E 51.10  C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10" Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	HILLOX WIC.
C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10" Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
C. Description of monument for corner and accessories established to perpetuate locating the poset Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10" Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
C. Description of monument for corner and accessories established to perpetuate locating the positive set Roscommon County Std. Mon Stamped G - 8  Spike in 8" Cedar N35°W 67.77  Spike in 10" Cedar N3°W 75.41'  Spike in 12" Cedar N19°E 54.11  Nail & tag in 10" Cedar S26°E 51.15  Carsonite post set 33.0 North	
Set Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10"Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Set Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10 Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Set Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10"Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Set Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10 Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Set Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10 Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Set Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10 Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Set Roscommon County Std. Mon Stamped G - 8 Spike in 8" Cedar N35°W 67.77 Spike in 10"Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	osition of the corner:
Spike in 8" Cedar N35°W 67.77 Spike in 10 Cedar N3°W 75.41' Spike in 12" Cedar N19°E 54.11 Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	and the second second
Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	OF MICH
Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	SE CONTRACTOR OF THE PROPERTY
Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Nail & tag in 10" Cedar S26°E 51.15 Carsonite post set 33.0 North	
Carsonite post set 33.0 North	ARLETH (5)
	SURVEYOR FE
	NO. 152
	21266
	A. V. S.
	OFESSION
	0=
signed by Mars Mars Date ZZ	WEC 75
Signed by	
	BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28. REVISED MAY 14.
Date December 14, 1893 Peer Group Approved	REVISEO JAN.
EIBER 3 PAGE 75	