JAN 2 & 1996

## LAND CORNER RECORDATION CERTIFICATE

Far assument in	COMVRITING Require	ement of Act 74, Mich. P.		
For corners in Roscommon (County)	Located In:	Corner Code #	ROSCONHON COUNTY RECORDED	
Public Land Survey     Property Controlling	T24N R _4W T R T R T R ST R	Constant C	14 AUG 95 3:48 P.M.  ROBERT W. SHITH  REGISTER OF DEEDS	
in Section 3. Miscellaneous Property in Section	S T R S T R S T R	APR 0 5 1996	To Be filed in Liber 3 of Land Corne Register of Deeds Stamp & File Number	
4. Lot No, Rec 5. Private Claims		COMMISSION	2 6 5 4 3 2 3 3 3 3 4 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	
do hereby certify that under require in lines 1 and 2 above were in commanual of survey instructions of Management or by a decree of a 5 above were in conformance will becree of a Court of Law; established expressed below:	rements of P.A. 74, Michigan P.A. formance with regulations and roof the United States Departm Court of Law and/or that the count of the rules of the Michigan Bo	A. of 1970, the corner points mentrules therefore as required in the chent of the Interior, Bureau of briner points mentioned in lines 3, pard of Professional Surveyors of	ntioned current f Land 7	
NOTE: Not more than 4 corne on this certificate.	ers, all in the same town and	I range, may be recorded	11 12 -31 13 -32 -33 -34 -35 -36 -36	
A. Description of original me	onument and accessories a	nd/or subsequent restoration	on:	
GLO-A.P. Brewer Mon-Post WIT: 18" Y.Pine NO2°W 38 1 18" Y.Pine S41°W 8 1	Mon-la <sup>i</sup> Bar in   lks. WIT: Fence on	North	MDOT Lyle Schalgried Mon-Fd. 같' Iron Pin WIT: P.P. N68°W 77.70' P.P. N51°E 36.05'	

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found  $\frac{1}{2}$  x 24 Bar in intersection of road. Replaced with standard Roscommon County Monument.

L.314, pg.401 F.J. Arleth Feb. 27, 1976 Mon-Fd. ½" Bar

**ROSCOMMON COUNTY PEER GROUP APPROVAL** DATE AUG 8th 1995

**County Surveyor** 

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G.D. Henning Oct. 1948 Mon-Cor. shown with no description of type

of Mon. WIT: None Given

Mon-Std. Roscommon County Monument
WIT: Fd. Nail & MSHD NW side new P.Pole N56°E 36.05'
Fd. Nail in N. face 10" Spruce S46°E 44.85'
Fd. Spike in NW face 3" Cherry S55°W 47.05'
Fd. MSHD Nail & Tag N68°W 77.75'
On Old Fence Line North

OF MICHIO aarvin e MYERS Pier.

Surveyor's Michigan License No.

REVISED MAY 14, 1975 REVISED JAN., 1983