

12-7-94 302

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Libers 6 Page 266

For corners in
Saginaw

SURVEY &
REMONUMENTATION

Located In:

Corner Code =#

1. Public Land Survey T 12 N R 3 E.

K-1

APR 24 1995

COMMISSION

2. Property Controlling S T R

3. Miscellaneous S T R

Property in Sec. S T R

4. Lot No. , Recorded Plat

5. Private Claims

RECORDED & FILED
DEC 27 9 16 AM '94
MICHIGAN REGISTER OF DEEDS
SAGINAW COUNTY MICH.

Register of Deeds Stamp & File Number

I, Ronald C. Prevost, in a field survey on December 6, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-1 Post by Joseph Wampler 1822
Hickory 14" S.22°W. 25 Lks.
Sugar 12" N.78°E. 11 1/2 Lks.
Stone with 3/4" pipe over, 1941 Redmond notes, NE 24" Maple 77.00, NW fence post hole in concrete 34.0
SCRC witnesses 1974, 3/4" pipe

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-1 Found 3/4" Pipe in Mon. Box

Is accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-1 Placed 5/8" rerod & 2 1/2" Saginaw Co. Bronze Cap in existing Mon. Box in location of 3/4" pipe
East 23.86 3/4" bar corner K-13, T.13 N.-R.3 E.
N.65°E. 76.21 nail & washer SE face 30" Maple (Redmond NE 24" Maple 77.0)
S.45°W. 42.50 nail E face P.P. (SCRC N.55°E. 36" Maple 76.78)
N.10°W. 61.06 SE corner post chain link fence
S.40°W. 56.0 center hydrant

Signed by Ronald C. Prevost

Date 12-15-97

Surveyor's Michigan License No. 24612

