

# **SURVEY & REMONUMENTATION**

AUG 05 1996

**COMMISSION**

LIBER 1887 PAGE 631

Liber 6 Page 158

## **LAND CORNER RECORDATION CERTIFICATE** Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Saginaw

(County)

Located In:

Corner Code #

1. Public Land Survey

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

2. Property Controlling in Section

S 1 T 12N R 4E

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

3. Miscellaneous Property in Sec.

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

RECORDED  
in File  
Dec 8 3 30 PM '93

MILDRED M. DODAK  
REGISTER OF DEEDS  
SACINAW COUNTY MICH.

Register of Deeds Stamp & File Number

I, Brian D Ferguson, in a field survey on December 1, 19 93

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-2.3 Wood post set by J. Wampler in 1822, at intersection of East Section line with NW'ly line of Peter Riley Reserve line.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-2.3 No evidence of original reserve line exists. Universal Drain (open drain) now occupies this line. Reserve line has been monumented by points where roads cross said line. Set 3" brass disk 35.00 feet N'ly of reserve line on East Section line and is accepted as the best available evidence of the position of the original corner. Accepted by the Peer Review Group on 11/12/93

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


M-2.3 3" Brass Disk (858.38' S'ly of M-2)

S02°W 12.10' Top ctr of 12" CMP  
N50°W 6.00' Top ctr of 12" CMP  
N45°W 15.79' Nail & tag in E fce 12" stump  
N45°E 11.68' Nail & tag in S fce 6" tree  
N70°E 14.41' Nail & tag in N fce 6" tree  
West 4'± Center line 10' wide ditch running N-S  
South 27'± Center line Universal Drain running NE-SW

Signed by

Surveyor's Michigan License No.

Date



FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1976  
REVISED JAN., 1983