## LIBER 1986 PAGE 503

APPROVED BY PEER GROUP Saginaw County R. P.A. 345 OF 1990 LAND CORNER RECOR SAGINAW COUNTY Filing Requirement of A	emonumentation	ATE LI	Ser ?	Page 9
SAGINAW COUNTY Filing Requirement of A	ct 74, Mich. P.A. 19	70		
For corners in 8 - 20 - 96 / AC Saginaw Located In: Corner Code #		SAGII	REG REG	_ recoupep % elted
(County) Kochville Township				COR
1. Public Land Survey T_13NR_4E		( )		<u> </u>
TR TR	<del></del>		9. <del>5</del>	<u>∞</u>
τ <u> </u>		<u> </u>	SAN ISS	골
2. Property Controlling S T R	<del></del>	5		8
in Section S T R			· com	
Property in Sec. S T R		Danietar of	Doode Stom	s & File Number
		Trograter or	Decus Stains	7 & File Mullipel
4. Lot No, Recorded Plat				
5. Private Claims		1 B C D	EFGH	IJKLN
		2 - 6 - 5		3
Nichard I MarBarell I St. St. Accorded 4000		3		
I, Michael J. MacDonald , in a field survey on August 16, 19 96 de requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in line	o hereby state that under s 1 and 2 above were in	4 7 8		0- -1112
conformance with regulations and rules therefore as required in the current manual of united States Department of the Interior, Bureau of Land Management or by a decree	survey instructions of the	5	1,6	
that the corner points mentioned in lines 3, 4 and 5 above were in conformance with	the rules of the Michigan	6 18 17	161	5 14 13
Board of Land Surveyors or by a Decree of a Court of Law; established, re-es recovered, found as expressed below:	tablished, monumented,	8 19 20	212	2 23 24
NOTE: Not more than 2 corners, all in the same town and range, may be rec	ardad	9		
on this certificate.	·	10 30 29	282	7-26-25
		11		
		12 31 32	33	4 35 36-
		13		
A. Description of original monument and accessories and/or subsequent r	estoration:			
				4
C-7 Post set by J. Wampler D.S. in 1840.	L.C.R.C L. 2, P. 177, Recorded Surveys - L	, J. Martin 3/8" pi 674. P. 322: 1 . 1	pe. (Bay Count	ty) Say County)
L.C.R.C L. 1721, P. 217, D. Ledy fnd 1/2" pipe. (Saginaw County)	· · · · · · · · · · · · · · · · · · ·	07 4, 1 . OZZ, E.	1000, F. 130. (L	say County)
<u>L.C.R.C.</u> - L. 2, P. 111, J. Martin 1/2" pipe. (Saginaw County) <u>Recorded Surveys</u> : L. 1721, P. 224; L. 1446, P. 687; L. 1392, P. 588.				
(Saginaw County)  Bay County Road Commission Notes (undated) - fnd 3/8" pipe.				
- The did pipe.				
B. Description of corner evidence found and/or method applied in restoring	g or reestablishing corn	er:		
C-7 Fnd 3/8" I.D. pipe in monument box.	S 76.70' to 1/2" iron rod in centerline Seven Mile Road as recorded in J&A road plans for Bay County Road Commission.			
Recorded Witnesses as follows: SW 70.82' (70.75' - R) to RR spike In pole.	Monument accepted a of the original corner.	s the best availab	ole evidence of	the position
NW 43.60' (43.47' - R) to spike in pole.	or are original corner.			
E-SE 111.00' to nail and tag in pole (111.30' - R to RR spike).				
•				
C. Description of monument for corner and accessories established to per	netuate leasting the nesi	itian af tha sarns	<b>.</b>	
. Description of mortalitation comes and accessories established to per	percare rocaulig the pos	don of the come		OF MICH
C-7 Replaced 3/8" pipe with Bay County Remonumentation cap on			# 5 P	OF MICHICAL
5/8" x 24" long rebar in monument box.			* * N	IICHAEL J. 🦎 🛭
N 40° E 91.65' to top center of hydrant.			No.	SCDONALD
S 80° E 111.00' to nail and tag in SW face of pole.  N 45° W 43.96' to nail and tag in NE face of pole.			95	SURVEYOR 🦸
S 45° W 71.17' to nail and tag in NW face of pole.			A SE	No. 22438
•			S N N N N N N N N N N N N N N N N N N N	OFESSIONAL STATE
			786	ANTHONIO PORTOR
Signed by Milder of Marchand	Date	Sept o	6	
Surveyor's Michigan License No. 22430	Date	·	=	
Secretary C				
man de la maria de la companya del companya de la companya del companya de la com	FADIA ADDONASTO DA MASSOCIO	N OTATE DO LOG OF	MACES COMMITTEE	DUDYODO INVICE ICT
	FORM APPROVED BY MICHIGA	N SIATE BOARD OF F	HUTESSIONAL SUI	REVISED MAY 14,1975
MAY <u>1</u> 8 1997				REVISED JAN., 1983 REVISED OCT., 1995

MAY 1 8 1997

Succession Color