

SAGINAW COUNTY REMONUMENTATION

RECORDED/FILED

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

1999 SEP 29 A 8:07

MILDRED M. DODAK  
REGISTER OF DEEDS  
SAGINAW COUNTY, MI.

LIBER 2144 PAGE 780

*Liber 8 Page 45*

Register of Deeds Stamp & File Number

For corners in

KOCHVILLE TOWNSHIP

SAGINAW  
(County)

Located In:

Corner Code #

1. Public Land Survey T13 N R 4 E L-9  
T R  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

4. Lot No. , Recorded Plat  
5. Private Claims

I, Brian D Ferguson, in a field survey on JUNE 26, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2				
3													
4	7		6		5		4		3		2		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

WOOD POST SET BY J. WAMPLER IN 1822, NO EVIDENCE OF ORIGINAL CORNER REMAINS  
LCRC BY JOHN MARTIN IN 1973, L 2, PG 100  
LCRC BY JOHN MARTIN IN 1977, L 4, PG 75  
RECORDED SURVEYS, L 1921, PG 2285; L1767, PG 1661; L 1611, PG 1956; L 1717, PG 158

RECORDED &  
MAR 09 2000

SECTION

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4" PIPE IN MONUMENT BOX PER LCRC'S AND RECORDED SURVEYS. VERIFIED LOCATION BY DISTANCES TO ADJOINING CORNERS FROM RECORDED AND UN-RECORDED SURVEYS.

ACCEPTED BY PEER GROUP AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 5/8" REBAR W/ 3" BRASS CAP IN MONUMENT BOX  
N50E 30.10' NAIL W/MDOT CAP IN PWR POLE  
S45W 51.75' NAIL W/MDOT CAP IN PWR POLE  
S40E 66.23' TOP CTR OF HYDRANT  
N40W 50.70' TOP CTR OF HYDRANT

Signed by Brian D Ferguson  
Surveyor's Michigan License No. 26454

Date SEPTEMBER 23 1999

