

APPROVED BY PEER GROUP
P.A. 345 OF 1990
SAGINAW COUNTY

9-22 BDF

SAGINAW COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED/FILED

1999 SEP 29 A 8:08

MILDRED M. DODAK
REGISTER OF DEEDS
SAGINAW COUNTY, MI.

LIBER 2144 PAGE 782

Lib 8 Page 47

Register of Deeds Stamp & File Number

For corners in

SAGINAW
(County)

KOCHVILLE TOWNSHIP

Located in:

Corner Code #

1. Public Land Survey

T13N R4E

M-9

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Brian D Ferguson, in a field survey on JUNE 26, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

WOOD POST SET BY J. WAMPLER IN 1822, NO EVIDENCE OF ORIGINAL CORNER REMAINS
LCRC BY JOHN MARTIN IN 1972, L 1, PG 240 (RECORDED AS A-9 IN T13N-R5E. CORNER IS COMMON
RECORDED SURVEY IN L 1349, PG 448

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4" IRON ROD PER LOCATION FROM RECORDED SURVEY. LCRC WITNESSES GONE

SURVEY &
RF

MAR 9 2000

SECTION

ACCEPTED BY PEER GROUP AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 5/8" REBAR W/ 3" BRASS CAP IN MONUMENT BOX
S55E 35.22' SET REBAR 1.5' SOUTH OF ROAD
N50E 33.20' SET REBAR 1.5' NORTH OF ROAD
S25W 21.66' EAST LEG ROAD DIRECTION SIGN
NORTH 65.11' NAIL IN TOP OF WOOD GUARDRAIL POST

Signed by Brian D Ferguson
Surveyor's Michigan License No. 26454

Date _____

