

JAN 22 2001

2000 Remonumentation Program

RECEIVED FOR RECORD

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

00 NOV 27 AM 8:55

For corners in

Sanilac Located In: Corner Code #
(County)

1. Public Land Survey T11N R15E J - 1
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

LIBER NO. 3 PAGE NO. 34
MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

2000
I, John A. Millettics, in a field survey on May 1, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO Notes - None
Act 132 - None
Old Survey Liber - None
Unrecorded surveys - Millettics Nov 1990 - Millettics March 1993
Millettics Dec 1996 - Millettics March 1999
L.C.R.C. Forms - None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J - 1
N 1/4 Corner Section 2 T11N-R15E
Found 1/2" Iron Bar in Monu Box
West 2676.92 feet to the NW Corner Section 2
East 2667.60 feet to the NE Corner Section 2
Accepted as best evidence

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J - 1
N 1/4 Corner Section 2 T11N-R15E
1/2" Iron Bar in Monu Box
East 6.12 feet to the N 1/4 Corner Section 35
S05°W 42.35 feet to the NE Corner of a House
S05°E 18.10 feet to a nail in a Power Pole
S65°E 44.20 feet to a nail in a 36" Maple
North 7.4 feet to the center of M- 46
N05°E 65.10 feet to a nail in a Power Pole
N10°E 67.45 feet to a R/W Marker
East 2667.60 feet to the NE Cor Sec. 2 - West 2676.92 feet to the NW Cor Sec. 2

APPROVED PEER BOARD
MEETING NOV 25 2000



igned by John A. Millettics Date Nov 15, 2000
urveyor's Michigan License No. 25859