

JAN 22 2001

SECTION

LIBER

3 PAGE 30

2000 Remonumentation Program
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD

09 NOV 27 AM 8:55

LIBER NO. 3 PAGE NO. 30

MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

For corners in

Sanilac

(County)

Located In:

Corner Code #

1. Public Land Survey

T 11N R 15E

J - 7

T R

T R

T R

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

John A Milletics, in a field survey on May 1, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

GLO Notes

Beech 9" S28°W 5 Links

Beech 7" N07°E 14 Links

Act 132 - Liber 2 Page 470 I.E. Chope April 1974

Old Survey Liber - None

Unrecorded surveys - Milletics 1998

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J - 7

S 1/4 Corner Section 14 T11N-R15E

Found 1/2" Iron Bar with cap

West 2653.96 feet to the SW Corner Section 14

East 2659.54 feet to the SE Corner Section 14

Accepted as best evidence

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J - 7

S 1/4 Corner Section 14 T11N-R15E

1/2" Iron bar with cap in old fence row

S45°E 55.70 feet to a nail in a Power Pole

S10°E 34.10 feet to a nail in a wooden fence post

South 16.60 feet to a nail in a wooden fence post

N10°E 13.10 feet to a nail in a 10" Cherry tree

West 2653.96 feet to the SW Corner Section 14

East 2659.54 feet to the SE Corner Section 14

APPROVED PEER BOARD
MEETING NOV 25 2000

91

igned by John A Milletics
urveyor's Michigan License No. 25859

Date Nov 15, 2000

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

